Esprit A Class



The Esprit combines modern Nordic-style design with excellent top-class comfort. Its heatable double floor with frost-proof water installation makes it a winter-proof year-round companion. With a height of 26 cm, it offers usable additional storage space.

Technical info	
Overall length, approx.	779 cm
Overall width, approx.	232 cm
Overall height, approx.	298 cm
Headroom in living area, approx.	205 cm

Maximum values partly not possible for all models or only in connection with certain options.

Upholstery



+ Upholstery Kari



+ Upholstery Nubia



+ Rubino real leather upholstery



+ Real leather individual O

Wood décor



+ Wood décor Noce Nagano

O optionally available

Plus factors

- 180 hp (136 kW) Multijet engine, 8-speed torque converter automatic transmission, automatic climate control, multifunction leather steering wheel and much more.
- + Ideal driving characteristics: Premium low platform chassis with 145 mm lowering and up to 4.5 t gross vehicle weight
- + Absolute winter resistance due to heated raised floor with installation laid frost-protected
- + Lifetime Plus superstructure technology with absolutely rot-proof and durable wall construction
- + Spacious rear garage, with doors on both sides, 250 kg surface load, anti-slip floor covering, fleece lining, lashing rails, lighting as well as one-hand operation and 2-point locking system
- + Gourmet kitchen with 3-burner stove, generous drawers with soft-close retraction and central locking, cutting board, apothecary pull-out, and much more.
- + Large, comfortable pull-down bed with 200 x 150 cm lying surface, high-quality cold foam mattress and wooden slatted frame. Electrically operated



























Esprit A Class Technical info









Esprit A Class	I 7150-2 EB	I 7150-2 EBL	I 7150-2 DBM	I 7150-2 DBL
Standard chassis	Fiat Ducato Maxi AL-KO Low Platform	Fiat Ducato Maxi AL-KO Low Platform	Fiat Ducato Maxi AL-KO Low Platform	Fiat Ducato Maxi AL-KO Low Platform
Emission standards	Euro VI-E	Euro VI-E	Euro VI-E	Euro VI-E
Overall length, approx. cm	779	779	779	779
Overall width, approx. cm	232	232	232	232
Overall height, approx. cm	298 1)	298 1)	298 1)	298 1)
Headroom in living area, approx.	205	205	205	205
Towable load braked/ unbraked kg	1750 / 750	1750 / 750	1750 / 750	1750 / 750
Wheelbase, approx. mm	4500	4500	4500	4500
Bed dimension: Front bed, L x W, approx.	200 x 150	200 x 150	200 x 150	200 x 150
Bed dimension: Central / middle bed, L X W, approx. cm	206 x 123 - 88 O		206 x 123 - 88 O	
Bed dimension: Rear bed, L x W, approx.	215 x 80 / 220 x 80 / 210 x 200 - 193	215 x 80 / 220 x 80 / 210 x 200 - 193	200 x 160	200 x 160
Sleeping berths standard / max.	4 / 5 🔾	4	4 / 5 🔾	4
Standard engine	180 MultiJet 3 Power	180 MultiJet 3 Power	180 MultiJet 3 Power	180 MultiJet 3 Power
kW (bhp)	132 (180)	132 (180)	132 (180)	132 (180)
Mass in running order (+/-5%)* kg	3450 (3278 to 3623)*	3530 (3354 to 3707)*	3450 (3278 to 3623)*	3480 (3306 to 3654)*
Manufacturer-specified mass for optional equipment* kg	447	377	447	427



* INFO

The specified mass in running order is a default value defined in the type-approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to \pm 5 % of the mass in running order are legally permissible and possible. The permissible range in kilograms is given in brackets after the mass in running order. The manufacturer-specified mass for optional equipment is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. The limitation of optional equipment is intended to ensure that the minimum pay-mass, i.e. the legally prescribed free mass for baggage and retrofitted accessories, is actually available for the vehicle load capacity of the vehicles delivered by Dethleffs. The real weight of your vehicle ex works can only be determined when it is

weighed at the end of the line. If, in exceptional cases, the weighing shows that the actual load capacity falls below theminimum pay-mass despite limiting the optional equipment due to a permissible weight deviation, we will check together with your trade partner and you whether we should, for example, increase the load capacity of the vehicle, reduce the number of seats or remove optional equipment before delivering the vehicle. The technically permissible maximum laden mass of the vehicle and the technically permissible maximum mass on the axle must not be exceeded. Detailed information & explanations on the subject of weight and the configuration of the vehicle can be found in the section Legal information. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes.

Esprit A Class Technical info









Esprit A Class	I 7150-2 EB	I 7150-2 EBL	I 7150-2 DBM	I 7150-2 DBL
Technically permissible maximum laden mass* kg	4250	4250	4250	4250
Permitted number of seats (including driver)*	4 - 5 🔿	4	4 - 5 O	4
Refrigerator volume (thereof freezer), approx.	136 (23) / 177 (35) 🔾	136 (23) / 177 (35) O	136 (23) / 177 (35) 🔾	136 (23) / 177 (35) 🔿
Waste water tank, approx.	156	156	156	156
Fresh water tank capacity, total/ Fresh water tank capacity at driving filling	166 / 20	166 / 20	166 / 20	166 / 20
Measurement storage opening left (W x H) cm	100 x 80 O / 100 x 110	100 x 80 O / 100 x 110	100 x 105	100 x 105
Measurement storage opening right (W x H) cm	100 x 80 O / 100 x 110	100 x 80 O / 100 x 110	100 x 105	100 x 105

O Optional equipment — Not possible • Standard equipment • Mandatory A Not known at the time of publication



The specified mass in running order is a default value defined in the typeapproval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to ± 5 % of the mass in running order are legally permissible and possible. The permissible range in kilograms is given in brackets after the mass in running order. The manufacturer-specified mass for optional equipment is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. The limitation of optional requipment is intended to ensure that the minimum pay-mass, i.e. the legally prescribed free mass for baggage and retrofitted accessories, is actually available for the vehicle load capacity of the vehicles delivered by Dethleffs. The real weight of your vehicle ex works can only be determined when it is

weighed at the end of the line. If, in exceptional cases, the weighing shows that the actual load capacity falls below theminimum pay-mass despite limiting the optional equipment due to a permissible weight deviation, we will check together with your trade partner and you whether we should, for example, increase the load capacity of the vehicle, reduce the number of seats or remove optional equipment before delivering the vehicle. The technically permissible maximum laden mass of the vehicle and the technically permissible maximum mass on the axle must not be exceeded. Detailed information & explanations on the subject of weight and the configuration of the vehicle can be found in the section Legal information. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes.

Standard equipment

| 7150-2 EB | 7150-2 EBL | 7150-2 DBM | 7150-2 DBL

lloy wheel Fiat 16 " at Ducato Maxi ALKO low platform wide-track rear axle (4,250 kg) MultiJet 180 (2.2 / 132 kW / 180 hp) Heavy Duty, 8-speed torque onverter automatic transmission at chassis features	•	•	•	
onverter automatic transmission				
at chassis foaturos		•	•	•
of Chossis reduites				
BS (anti-lock braking system) / EBD (electronic brakeforce distribution)	•	•		•
dditional protection for radiator through grille at front of vehicle	•	•		•
nti-theft device		•		
utomatic Brake Assist after a collision	•	•	•	•
utomatic cab air conditioning, digital speedometer with 7" instrument cluster and wireless phone charger in the centre console				
aptain seat with integrated headrest, rotatable, height and tilt adjustable incl. two padded armrests	•	•		•
rosswind Assist		•		
uise control	•	•	•	•
up holder in the centre of the dashboard		•		
ashboard with aluminium application		•		•
iesel tank 90 litre incl. 19L AdBlue tank	•	•	•	
river and passenger airbags				
river and passenger detection		•		
SP incl. ASR, Traction Plus, Hill Holder and Hill Descent Control				
ont-wheel drive		•		
eather steering wheel and gear knob withleather sleeve				
ow-vibration coach-style exterior mirrors that can be heated and adjusted electrically (two-piece)		•		
eated privacy blind in the windscreen can be adjusted horizontally and laterally for the best insulation				
reering wheel with control elements				
ailer Stability Assist	•	•	•	•
re inflation kit and towing eye				
inter tyres M+S Camping (with snowflake)	•	•	•	•
cterior features				
ethleffs Exclusive rear light carrier with ShapeLine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall	•	•	•	•
cm wide habitation door with window and blind				
edroom window right and left		•	•	•
ouble floor storage, some of which can be loaded across almost the entire vehicle width		•		
ouble-glazed flush-fitting windows with blackout & mosquito protection	•	•	•	
river's cab door left			•	
ectric closing aid for habitation door				•
oor thickness: 43 mm, side wall thickness: 34mm and roof thickness: 35 mm			•	
yscreen habitation door	•	•	•	•
RP roof				
abitation access with comfortable coupe entrance	•	•	•	•
abitation access with comfortable, wide, electric step				
fetime Plus construction technology: rot-free superstructure with no wood inserts, XPS insulation with GRP cladding on the underslung and of	•	•	•	•
anoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed				
ear garage: two garage door with one-hand operation, rear lowering (250 kg), heated, lashing rails, LED lights across the entire width, 230 V ocket, GRP anti-slip flooring and fleece cove	•	•	•	•
de panels and rear panel in smooth aluminium sheets				
cylight 40 x 40 cm above the seating lounge	•	•	•	•
cterior design				
cterior body painted in white	•	•	•	•
iterior design				
		•		
pholstery Kari	_	_		
pholstery Kari Yood décor Noce Nagano				

Standard equipment	I 7150-2 EB	I 7150-2 EBL	I 7150-2 DBM	1 7150-2 DBL
ear beds with ergonomic wooden slatted frames and 150 mm thick 7-zone premium mattresses made of climate-regulating material	•		•	•
urniture layouts				
irPlus overhead locker rear ventilation to avoid condensation				
osy L-shaped lounge with free-standing, rigid table base and two integrated 3-point seatbelts		_		
osy lounge seating group with free-standing, rigid table base			_	
ouble bed high	_	_		
lectric pull-down bed in the driver's cab	•			
loor-to-ceiling wooden sliding door to the bedroom	•			•
igh-level single beds incl. comfortable access via steps	•		_	_
lo steps in living room	•	•		•
iption to convert single beds to double bed	•		_	_
verhead locker doors with soft-close function	•	•	•	•
verhead lockers in the rear area	•		_	_
hoe cabinet in entrance area	•	•	•	•
Vardrobe to the left and right of the queen-size bed	•			
itchen				
loor-to-ceiling fridge with separate freezer compartment and automatic energy selection (AES) (136 l)				
ourmet kitchen: three-ring hob, large drawers with soft-close function, cutting board, apothecary drawers, waste bin and central locki	ing •			
rathroom	g	Ť	Ť	Ť
11 - 11				
quipped with cabinets, storage compartments, hooks, large mirrors and a height-adjustable shower head	•			
arge bathroom with separate shower and toilet with locking door to the lounge	•			
hower grate		_		
hower grate hower panel and bathroom accessories in black				
Vindow in bathroom				
leating				
igital control element for hot-air heating	•			
as hot-air heating 6kW with hot-water boiler	•	•	•	•
leating in the seating unit for optimum heat distribution, built-in	•	•	•	•
lectrical installation				
utomatic switch-on/disconnect for starter battery, leisure battery and refrigerator	•			
wning light 12 V	•			
lectric block with integrated overvoltage protection and separate ground fault circuit breaker	•			
ED lighting throughout the vehicle	•	•	•	•
eisure battery AGM, 95 Ah	•			
uxus on-board control panel	•	•	•	•
lumber of sockets 1x 12V, 7x 230V, 2x USB	•	•		
potlights in the roof lining above the habitation door	•	•	•	•
Vater supply				
ressurized water pump system	•	•	•	•
witch for water pump		•		
ias supply				

PACKAGES ESPRIT A CLASS

Package	Dual Battery System Package 1 (7488)	Dual Battery System Package 2 (7489)
Victron PowerAssist and PowerControl	X	Х
Electric block EBL 102	X	Х
Victron control panel above the habitation door	Х	Х
Victron Energy MultiPlus charging/inverter combination 1600W/70A	Х	
168 Ah lithium battery	Х	
Victron Energy MultiPlus charging/inverter combination 3000W/120A		Х
336 Ah lithium battery		Х
Additional weight (kg)*	63	113

Travel Package (14584)

Preparation for radio system incl. sound package in the driver's cabin

DAB+ radio antenna mounted on the roof

Panoramic skylight 75x105 cm above the seating lounge

Light Moments: Indirect ambient lighting above the overhead lockers

Rear corner steadies (2 pieces)

Electric windscreen blinds

Automatic gas cylinder switchover incl. crash sensor, EisEx and gas filter

Extractor fan (extracted air) with draught stopper

Integrated single-lens rear view camera

Central locking for the drive's cab, habitation and garage door

Additional weight (kg)* 48.5

Light Moments (11137)

Light Moments: Illuminated entrance handle

Light Moments: Indirect lighting in the bathroom with illuminated shower panel

Light Moments: plinth lighting throughout the vehicle Light Moments: Continuous canopy with indirect lighting

Light Moments: illuminated kitchen splashback

Light Moments: Indirect dimmable wall surface ambient lighting

Additional weight (kg)*

Esprit GT (14585)

LED low beam

Lateral sun shades, as a roller blind for driver and passenger

Panorama skylight 70 x 50 cm in the bedroom

Interior design GT incl. extended kitchen back panel

Exterior design GT Advance (rear light moulding with black diffuser, I-front paint partially black, radiator grille with chrome piping, skidplate "red")

High characteristic Dethleffs Exclusive rear light carrier with ShapeLine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall.

Additional weight (kg)* 15.7



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for

optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and explanations on the subject of weight can be found in the Legal information sortion.

Pre-wiring kit (11350)

Pre-wiring for solar

Pre-wiring for roof A/C

Pre-wiring for satellite system

Pre-wiring for first rear view camera

Pre-wiring for second rear view camera

Additional weight (kg)* 7.6

 \triangle Not known at the time of publication



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for

optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and explanations on the subject of weight can be found in the Legal information section.

Optional equipment*	Included in package	Additional weight (kg)*	Code	I 7150-2 EB	I 7150-2 EBL	I 7150-2 DBM	I 7150-2 DBL
Weight upgrade							
Weight upgrade 4,500 kg	_	0	1585	0	0	0	0
Fiat chassis features							
Additional seat ⁹⁾	_	17	435	0	_	0	_
Electric windscreen blinds	_	7	1782	0	0	0	0
Hydraulic lifting jacks with automatic levelling and weighing function	_	70	9663	0	0	0	0
LED low beam	GT	0.5	7152	0	0	0	0
Reinforced spring for front axle	_	3.75	1889	0	0	0	0
SKA captain seat with air suspension	_	20	7505	0	0	0	0
Seat heating and ventilation of the seat area ¹⁵⁾ 16)	_	0	11147	0	0	0	0
Tow bar (check permissible gross towing weight for trailer operation)	_	30	273	0	0	0	0
Exterior features							
Bike rack for 3 bikes (lowerable)	_	20.7	7482	0	0	0	0
Bike rack for 3 bikes (rear)	_	10.5	938	0	0	0	0
Omnistor cassette awning 5.0 m (manual)	_	40	697	0	0	0	0
Panoramic skylight 75x105 cm above the seating lounge	_	16.5	849	0	0	0	0
Interior design							
Real leather individual 15) 17)	_	0	9785	0	0	0	0
Rubino real leather upholstery ¹⁵⁾	_	0	10443	0	0	0	0
Upholstery Nubia	_	0	10442	0	0	0	0
Textile equipment							
Carpet, loose	_	8.2	851	0	_	_	_
Carpet, loose	_	10.7	851	_	_	_	0
Carpet, loose	_	10	851	_	0	_	_
Carpet, loose	_	9.7	851	_	_	0	_
Furniture layouts							
Bed construction seating group transverse incl. lowerable table base	_	15.3	1944	0	_	0	_
ISOFIX child seat bracket for third and fourth seat facing direction of travel	_	4	8125	0	_	0	_
Low single-beds for comfortable access and high headroom	_	20.5	510	0	0	_	_
Overhead lockers in the driver's cab instead of pull-down bed		-40	679	0	0	0	0
Kitchen							
Extractor fan (extracted air) with draught stopper	_	1.5	344	0	0	0	0
Fridge (177 l), can be opened on both sides, with integrated oven	_	16	290	0	0	0	0
Winter cover for refrigerator vents	_	0.3	282	0	0	0	0
Bathroom							
Ceramic toilet ¹⁸⁾	_	9.1	7243	0	0	0	0
Macerator toilet with waste-holding tank	_	44	1625	0	0	0	0
Multimedia							
32" Smart TV incl. flat screen holder	-	10	9807+325	0	0	0	0
Additional 22' flat screen incl. flat screen bracket	_	5.5	7490+1809	0	0	0	0
Automatic satellite system 85 Twin	_	16	1637	0	0	0	0
Dethleffs Naviceiver incl. DAB+, truck navigation, wireless Apple CarPlay and Android Auto ⁶⁾	_	3.65	9582	0	0	0	0



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for actional equipment change in the model programs. This is a calculated to the control of the selected optional equipment change in the model programs. This is a calculated to the control of the selected optional equipment in the model programs. optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and

explanations on the subject of weight can be found in the Legal information section. An increase of load capacity increases the manufacturer-specified mass for optional equipment. The increase results from the higher pay-mass due to the alternative chassis. The increased tare weight of the alternative chassis and, in particular, the weight for any mandatory heavier engine variants (e.g. 180 hp) must be deducted from this. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes. footnotes.

Optional equipment*	Included in package	Additional weight (kg)*	Code	I 7150-2 EB	I 7150-2 EBL	I 7150-2 DBM	I 7150-2 DBL
Flat screen 22" incl. flat screen bracket	_	5.2	1799+325	0	0	0	0
Flat-screen TV bracket	_	2	325	0	0	0	0
Second rear view camera in rear moulding	_	1	11541	0	0	0	0
Sound package in living area ⁶⁾	_	9	9964	0	0	0	0
Top View 360° HD camera ^{19) 20)}	_	4.5	7173	0	0	0	0
Heating							
Gas hot-air heating 6kW with 1.8kW electric heating element and hot-water boiler incl. digital control panel	_	1	330	0	0	0	0
Heat exchanger for hot-water heating ¹³⁾	_	7.5	565	0	0	0	0
Hot-water carpet for the driver's cab ¹³⁾	_	3.5	6709	0	0	0	0
Hot-water heating with boiler, automatic drain valve and shut-off valve for the sleeping area and digital control panel	_	40	761	0	0	0	0
Air Conditioning							
Roof A/C	_	38.5	609	0	0	0	0
Electrical installation							
Solar power system 100 watt	_	12.6	922	0	0	0	0
Water supply							
Outdoor shower installed in rear garage (hot/cold water)	_	2.4	1574	0	0	0	0
Gas supply							
Automatic gas cylinder switchover incl. crash sensor, EisEx and gas filter	_	2.5	1577	0	0	0	0
Outdoor gas socket gas pressure 30 mbar	_	1.3	878	0	0	0	0
Safety							
2 kg fire extinguisher	_	4	1878	0	0	0	0
Alarm system (for door with central locking)	_	0.5	322	0	0	0	0
Safe	_	4.7	323	0	0	0	0
Packages							
Dual Battery System Package 1 ⁷⁾	_	63	7488	0	0	0	0
Dual Battery System Package 2 ⁷⁾	_	113	7489	0	0	0	0
Esprit GT	_	15.7	14585	0	0	0	0
Light Moments	_	11	11137	0	0	0	0
Pre-wiring kit	_	7.6	11350	0	0	0	0
Travel Package	_	48.5	14584	0	0	0	0
Miscellaneous							
Registration documents (CoC papers)		0	15152	*	*	*	*

O Optional equipment ─ Not possible ● Standard equipment ♦ Mandatory △ Not known at the time of publication

GT GT Package



INFO

The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and

explanations on the subject of weight can be found in the Legal information section. An increase of load capacity increases the manufacturer-specified mass for optional equipment. The increase results from the higher pay-mass due to the alternative chassis. The increased tare weight of the alternative chassis and, in particular, the weight for any mandatory heavier engine variants (e.g. 180 hp) must be deducted from this. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes.

LEGAL NOTES ON WEIGHT-RELATED INFORMATION

The weight specifications and tests for **motorhomes** are uniformly regulated throughout the EU in EU Implementing Regulation No. 2021/535 (until June 2022: EU Implementing Regulation No. 1230/2012). We have summarised and explained the key terms and legal requirements from this **regulation** for you below. Our **dealers** and the Dethleffs configurator on our website offer you additional assistance in configuring your vehicle.

1. Technically permissible maximum laden mass

The technically permissible maximum laden mass of the vehicle (e.g. 3,500 kg) is a mass specification set by the manufacturer which the vehicle must not exceed. Information on the technically permissible maximum laden mass of the model you have chosen can be found in the technical data. If the vehicle exceeds the technically permissible maximum laden mass in everyday driving, this constitutes an administrative offence which may result in a fine.

2. Mass in running order

In simple terms, the mass in running order is the basic vehicle with standard equipment plus a legally fixed standard weight of 75 kg for the driver. This essentially includes the following items:

- the unladen weight of the vehicle together with the bodywork, including operating fluids such as greases, oils and coolants;
- the **standard equipment**, i.e. all equipment items that are included as standard in the factory-fitted scope of delivery;
- the fresh water tank filled to 100 % in driving mode (driving fill according to manufacturer's specifications;) and an aluminium gas cylinder filled to
- the fuel tank, which is 90 % full, including fuel;
- the driver, whose weight regardless of the actual weight is generally specified as 75 kg in accordance with EU law.

Information on the **mass in running order** can be found for each model in our sales documents. It is important to note that the value for **mass in running order** given in the sales documents is a default value determined in the **type-approval procedure** and verified by the authorities. It is legally permissible and possible for the **mass in running order** of the vehicle delivered to you to deviate from the nominal value stated in the sales documents. The legally permissible **tolerance** is \pm 5 %. In this way, the EU legislator accounts for the fact that certain fluctuations in the **mass in running order** occur due to variations in the weight of supplied parts as well as due to processes and weather conditions.

These weight deviations can be illustrated by means of an example calculation:

- Mass in running order acc. to sales documents: 2,850 kg
- Legally permissible tolerance of ± 5 %: 142.50 kg
- Legally permissible range of **mass in running order**: 2,707.50 kg to 2,992.50 kg

The specific range of permissible weight deviations can be found for each model in the technical data. Dethleffs makes great efforts to reduce weight variations to the minimum that is unavoidable for production reasons. **Deviations** at the upper and lower end of the range are therefore very rare; however, they cannot be completely ruled out technically, even

with all optimisations. The real weight of the vehicle and compliance with the permissible **tolerance** is therefore checked by Dethleffs by weighing each vehicle at the **end of the line**.

3. Mass of the passengers

The **mass of the passengers** is set a standard value of 75 kg for each seat provided by the manufacturer, regardless of the actual weight of the passengers. The **mass of the driver** is already included in the **mass in running order** (see no. 2 above) and is therefore not included again. In the case of a **motorhome** with four **permitted seats**, the **mass of the passengers** is therefore 3 * 75 kg = 225 kg.

4. Optional equipment and actual mass of the vehicle

Optional equipment (also: additional equipment) includes, according to the legal definition, all optional equipment parts not included in the **standard equipment** which are fitted to the vehicle under the responsibility of the manufacturer – i.e. ex works – and can be ordered by the customer (e.g. awning, bicycle or motorbike carrier, satellite system, solar system, oven, etc.). Information on the individual or package weights of the **optional equipment** that can be ordered can be found in our sales documents. **Optional equipment** in this sense does not include other **accessories** that are retrofitted by the **dealer** or you personally after the vehicle has been delivered ex works.

The mass of the vehicle in running order (see no. 2 above) and the mass of the optional equipment fitted to a specific vehicle at the factory are together referred to as the actual mass. You will find the corresponding information for your vehicle after handover under item 13.2 of the Certificate of Conformity (CoC). Please note that this specification also represents a standardised value. Since the mass in running order – as an element of the actual mass – is subject to a legally permissible tolerance of $\pm~5~\%$ (see no. 2), the actual mass may also deviate accordingly from the stated nominal value.

5. Pay-mass and minimum pay-mass

The installation of optional equipment is also subject to technical and legal limits: Only so much optional equipment can be ordered and fitted at the factory that sufficient free weight remains for baggage and other accessories ("pay-mass") without exceeding the technically permissible maximum laden mass. The pay-mass is calculated by subtracting the mass in running order (nominal value according to sales documents, see no. 2 above), mass of the optional equipment and the mass of the passengers (see no. 3 above) from the technically permissible maximum laden mass (see no. 1 above). The EU regulations stipulate a fixed minimum pay-mass for motorhomes, which must remain as a minimum for baggage or other non-factory-fitted accessories. This minimum pay-mass is calculated as follows:

Minimum pay-mass in kg ≥ 10 * (n + L)

Where: "n" is the maximum number of passengers plus the driver and "L" is the overall length of the vehicle in metres.

For a motorhome with a length of 6 m and 4 approved seats, the minimum pay-mass is therefore e.g. 10 kg * (4 + 6) = 100 kg.

To ensure that the minimum pay-mass is maintained, there is a maximum combination of optional equipment that can be ordered for each vehicle model. In the above example with a minimum pay-mass of 100 kg, the total mass of optional equipment for a vehicle with four permitted seats and a mass in running order of 2,850 kg should not exceed 325 kg:

3,500 kg technically permissible maximum laden mass

- 2,850 kg mass in running order
 - 3*75 kg mass of the passengers
 - 100 kg minimum pay-mass

325 kg maximum permissible mass of optional equipment

It is important to note that this calculation is based on the default value for mass in running order as defined in the type-approval procedure, without taking into account the permissible weight deviations for mass in running order (see no. 2 above). If the maximum permissible value for the optional equipment of (in the example) 325 kg is almost or completely exhausted, an upward weight deviation can therefore result in the minimum pay-mass of 100 kg being met mathematically using the default value for the mass in running order, although in fact there is no corresponding load capacity. Here, too, an example calculation for a vehicle with four seats, whose real weighed mass in running order is 2 % above the nominal value:

3.500 kg technically permissible maximum laden mass
- 2.907 kg real weighed mass in running order (+ 2 % compared to the stated value of 2,850 kg)
- 3*75 kg mass of the passengers

- 325 kg optional equipment (maximum permissible value) = 43 kg actual load capacity (< minimum pay-mass of 100 kg)

In order to avoid such a situation, Dethleffs further reduces the maximum permissible weight of the total **optional equipment** that can be ordered on a model-specific basis. The limitation of **optional equipment** is intended to ensure that the **minimum pay-mass**, i.e. the legally prescribed free mass for **baggage** and retrofitted **accessories**, is actually available for the **vehicle load capacity** of the vehicles delivered by Dethleffs. Since the weight of a specific vehicle can only be determined when it is weighed at the **end of the line**, in very rare cases a situation may arise in which the **minimum pay-mass** at the **end of the line** is not guaranteed, despite this limitation of **optional equipment**. In order to guarantee the **minimum pay-mass** even in these cases, Dethleffs will check together with your **trade partner** and you before delivery of the vehicle whether, for example, the vehicle is loaded up, seats are reduced or **optional equipment** is removed.

6. Effects of tolerances of the mass in running order on the pay-mass

Regardless of the minimum pay-mass, you should note that unavoidable production-related fluctuations in the mass in running order – both upwards and downwards – have a mirror-image effect on the remaining load capacity: If you order our example vehicle (see no. 3. above), for example, with optional equipment with a total weight of 150 kg, the calculated pay-mass based on the default value for the mass in running order is 275 kg. The load capacity actually available may deviate from this value due to tolerances and may be higher or lower. If the mass in running or-

der of your vehicle is, for example, permissibly 2 % higher than stated in the sales documents, the **load capacity** is reduced from 275 kg to 218 kg:

3.500 kg technically permissible maximum laden mass

2.907 kg $\,$ real weighed mass in running order (+ 2 % compared to the

stated value of 2,850 kg) 3*75 kg mass of the passengers

150 kg **optional equipment** ordered for the specific vehicle

= 218 kg sactual load capacity

As a precaution to ensure that the calculated pay-mass is actually given, you should therefore take the possible and permissible tolerances for the mass in running order into account when configuring your vehicle. We also recommend that you weigh the laden motorhome on a non-automatic scale before each journey and, taking the individual weight of the passengers into account, determine whether the technically permissible maximum laden mass and the technically permissible maximum mass on the axle are observed.