Globebus Go Low Profile



The next adventure is just a bend in the road away! The new Globebus Go is so compact and manoeuvrable that even narrow roads and low passages cannot stop it. This enables completely new travel and leisure experiences. On the other hand, it is amazingly spacious inside: with plenty of room to move around and storage space, a smart swivel bathroom and generous bed dimensions. By the way: if desired, the Globebus Go can also be upgraded to a real winter specialist!

Technical info	
Overall length, approx.	598 - 668 cm
Overall width, approx.	219 cm
Overall height, approx.	266 cm
Headroom in living area, approx.	190 cm

Maximum values partly not possible for all models or only in connection with certain options.

Polster



+ Upholstery Ravello



+ Upholstery Calypso incl. driver and passenger seat cover O



+ Upholstery Salerno incl. driver and passenger seat cover O

Plus factors

- + Agile and safe handling thanks to compact van dimensions with an external width of just 2.20 m and an external height of 2.66 m
- + Proven Lifetime body construction with GRP outer skin and excellent insulation
- + Winter campers choose the separately available Winter Comfort Package
- + Diesel heating with 6 kW heating capacity and 10 l hot water boiler
- + Electrically operated compressor refrigerator with perfect cooling performance
- + Pleasant sleeping comfort due to 150 mm thick 7-zone cold foam mattresses made of climate-regulating material and ergonomic wooden slatted frames











Wood décor



+ Wood décor Noce Nagano

O optionally available

Globebus Go Low Profile Technical info





Globebus Go Low Profile		T 15	T 45
Standard chassis		Ford Transit Low Platform	Ford Transit Low Platform
Emission standards		Euro 6e	Euro 6e
Overall length, approx.	cm	598	668
Overall width, approx.	cm	219	219
Overall height, approx.	cm	266 ¹⁾	266 ¹⁾
Headroom in living area, approx.	cm	190	190
Towable load braked/unbraked	kg	2200 / 750	2200 / 750
Wheelbase, approx.	mm	3300	3750
Bed dimension: Central / middle bed, L X W, approx.	cm	150 x 101 - 75 O	155 x 101 - 75 O
Bed dimension: Rear bed, L x W, approx.	cm	198 x 137 - 132	201 x 80 / 193 x 75 / 198 x 160 O
Sleeping berths standard / max.		2/30	2/30
Standard engine		2,0 l TDCi Ford EcoBlue	2,0 l TDCi Ford EcoBlue
kW (bhp)		96 (130)	96 (130)
Mass in running order (+/-5%)*	kg	2600 (2470 to 2730)*	2655 (2522 to 2788)*
${\it Manufacturer-specified mass for optional equipment}^*$	kg	725	683
Technically permissible maximum laden mass*	kg	3500	3500
Permitted number of seats (including driver)*		2 - 4 O	2 - 4 🔿
Refrigerator volume (thereof freezer), approx.	1	83 (10) / 131 (15) 🔿	83 (10) / 131 (15) 🔿
Waste water tank, approx.	I	95	95
Fresh water tank capacity, total/ Fresh water tank capacity at driving filling	I	115 / 20	115 / 20
Measurement storage opening left (W x H)	cm	65 x 90 🔿	65 x 75 O
Measurement storage opening right (W x H)	cm	35 x 90	60 x 95

O Optional equipment ─ Not possible ● Standard equipment ◆ Mandatory △ Not known at the time of publication



The specified mass in running order is a default value defined in the type-approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to $\pm\,5$ % of the mass in running order are legally permissible and possible. The permissible range in kilograms is given in brackets after the mass in running order. The manufacturer-specified mass for optional equipment is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. The limitation of optional equipment is intended to ensure that the minimum pay-mass, i.e. the legally prescribed free mass for baggage and retrofitted accessories, is actually available for the vehicle load capacity of the vehicles delivered by Dethleffs. The real weight of your vehicle ex works can only be determined when it is

weighed at the end of the line. If, in exceptional cases, the weighing shows that the actual load capacity falls below theminimum pay-mass despite limiting the optional equipment due to a permissible weight deviation, we will check together with your trade partner and you whether we should, for example, increase the load capacity of the vehicle, reduce the number of seats or remove optional equipment before delivering the vehicle. The technically permissible maximum laden mass of the vehicle and the technically permissible maximum mass on the axle must not be exceeded. Detailed information & explanations on the subject of weight and the configuration of the vehicle can be found in the section Legal information. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes.

Standard equipment

45

		_
Ford chassis		
Ford Transit Light low platform (3,500 kg), TDCi EcoBlue (2.0 l / 96 kW / 130 hp) Light Duty, 6-speed manual transmission	•	•
Steel rims 16" (236/65 R16) with wheel trims	•	•
Ford chassis features		
12' multifunction display with SYNC4		
70I fuel tank		
ABS, EBD, ESP, TCS, Hill Start Assist, Crosswind Assist, Safety Brake Assist, Rollover Protection Cab, Emergency Brake Support incl. Emergency Brake Ligl	ht •	
Cruise control		
Driver airbag		
Driver and passenger seat Pilot Chair with double armrest, swivelling		
Electric handbrake		
Exterior Colour Cab Frost White		
Exterior mirrors manually adjustable		
Fix&Go kit (tyre repair kit)		
Fog light		
Ford 6-speed manual gear box		
Front Park-Pilot system		
Front-wheel drive		
Lane Assist		
Leather steering wheel		
Passenger airbag		
Pre-Collision Assist, radar-based	•	
Rear axle mudflaps		
Rear view camera	•	•
Traffic sign recognition system		
Tyre pressure monitoring system	•	•
Exterior features		
60 cm wide habitation door		
70 cm wide habitation door		
Bedroom window right and left		
Dethleffs Exclusive rear light carrier with 3rd brake light EPS insulation		
Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm		
Floor unckness: 49 mm, side wan unckness: 34mm and roof unckness: 35 mm Flyscreen habitation door		
GRP roof		
Habitation access with comfortable, wide, electric step		
Large rear garage: right-hand garage door with turn/tighten lock, rear lowering (150 kg surface load), anti-slip surface, heated, lashing strips, illuminated, 1x 230 V socket		•
Lifetime construction technology: Tried-and-tested reliable flooring and superstructure with excellent insulation		
Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface		
Skylight 40 x 40 cm above the seating lounge		
Exterior design		
Exterior body painted in white	•	_
Interior design		
Upholstery Ravello	•	•
Wood décor Noce Nagano	•	•
Textile equipment		
Textile equipment Rear beds with ergonomic wooden slatted frames and 150 mm thick 7-zone premium mattresses made of climate-regulating material		
Rear beds with ergonomic wooden slatted frames and 150 mm thick 7-zone premium mattresses made of climate-regulating material	•	•
Rear beds with ergonomic wooden slatted frames and 150 mm thick 7-zone premium mattresses made of climate-regulating material Furniture layouts	•	•
Rear beds with ergonomic wooden slatted frames and 150 mm thick 7-zone premium mattresses made of climate-regulating material Furniture layouts Double bed high in the rear, transverse	•	
Rear beds with ergonomic wooden slatted frames and 150 mm thick 7-zone premium mattresses made of climate-regulating material Furniture layouts	•	-

Standard equipment

Seating group with hook-in and extendable table and a belt buck preparation	•	•
Kitchen		
Compressor refrigerator with freezer compartment (83 l)	•	•
Gourmet kitchen: two-ring hob, large drawers, cutlery tray, bin and generous worktop	•	•
MultiFlex rail system incl. hooks (further accessories via Dethleffs Original Accessories)	•	•
Bathroom		
Equipped with cabinets, storage compartments, large mirrors, toothbrush mug and toilet paper holder	•	•
Swiveling bathroom wall for optimal use of space	•	•
Heating		
Diesel hot air heating 6 kW with hot water boiler and integrated height kit	•	•
Heating in the seating unit for optimum heat distribution, built-in	•	•
Electrical installation		
Automatic switch-on/disconnect for starter battery, leisure battery and refrigerator	•	•
Awning light 12 V	•	•
Electric block with integrated overvoltage protection and separate ground fault circuit breaker	•	•
LED lighting throughout the vehicle	•	•
Leisure battery AGM, 95 Ah	•	
Number of sockets 1x 12V, 7x 230V, 4x USB	•	
On-board control panel	•	•
Spotlights in the roof lining above the habitation door	•	•
Water supply		
Fresh water tank in insulated and heated area	•	•
Submersible pump	•	•
Gas supply		
Storage space for a gas cylinder with a filling weight of 2.75 kg		

PACKAGES GLOBEBUS GO LOW PROFILE

Package	Comfort Package T 15 (13804)	Comfort Package T 45 (13804)
Air conditioning automatic incl. dust and pollen filter	Х	Х
Glove compartment, lockable	X	X
Interior package Trend Line	Х	Х
Side protection strips painted in car colour	Х	Х
Front bumper painted in car colour	Х	Х
High Series headlights with static cornering light	Х	X
Electrically adjustable and heated exterior mirrors	Х	X
Alloy wheel Ford 16" , black	Х	X
Habitation door with window incl. blackout and central locking (incl. cab door)	Х	X
Opening window in T-hood	Х	X
Cab blackout blinds	Х	X
Panorama skylight 70 x 50 cm in the living area	Х	Х
Upholstery Calypso incl. driver and passenger seat cover	Х	Х
Light Moments: Indirect wall surface ambient lighting	Х	Х
Light Moments: Indirect ambient lighting above the overhead lockers	Х	Х
Access locker door left	Х	
Access locker door left		Х
Option to convert single bed to double bed		Х
Additional weight (kg)*	42.3	48.3

Package	Package One (awning 3.0m) (14844)	Package One (awning 4.0m) (14844)
Automatic HD satellite system 65 Twin	X	Х
Flat screen 22" HD TV	X	X
Flat-screen TV bracket	X	Х
Omnistor cassette awning 3.0 m (manual)	X	
Omnistor cassette awning 4.0 m (manual)		Х
Additional weight (kg)*	43.5	50.5



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for

optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and explanations on the subject of weight can be found in the Legal information section.

Package	Winter Comfort Package hot-air heating Globebus Go T 15 (13272)	Winter Comfort Package hot-air heating Globebus Go T 45 (13272)
Insulated under-floor pipes	X	X
Switch for water pump	X	X
Diesel hot air heating 6 kW with 1.8 kW electric heating element incl. digital control element and integrated height kit	x	х
Waste water tank and pipes electrically heated	X	Х
Insulated waste water tank	X	
XPS insulation	X	
Insulated waste water tank		Х
XPS insulation		Х
Additional weight (kg)*	22.3	23.8

Pre-wiring kit (14843)

Pre-wiring for solar

Pre-wiring for roof A/C

Pre-wiring for satellite system

Additional weight (kg)* 5.6

△ Not known at the time of publication



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for

optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and explanations on the subject of weight can be found in the Legal information section.

	Included in	Additional	Code		
Optional equipment*	package	weight (kg)*			
				T 15	T 45
Ford chassis	-	-			
Ford Transit Light low platform (3,500 kg), TDCi EcoBlue (2.0 l / 121 kW / 165 hp) Heavy Duty, 8-speed			1/54		_
automatic transmission ²⁾		55	165A	0	0
Ford chassis features					
Tow bar (check permissible gross towing weight for trailer operation) ²⁾	_	48	273	0	0
Exterior features					
Access locker door left	_	8	331	0	_
Access locker door left	_	6	331	_	0
Bike rack for 3 bikes (lowerable)	_	21.1	7482	0	0
Bike rack for 3 bikes (rear)	_	9.6	938	0	0
Double-glazed flush-fitting windows with blackout & mosquito protection	_	1	415	0	0
Omnistor cassette awning 3.0 m (manual)	_	27	932	0	_
Omnistor cassette awning 4.0 m (manual)		34	859		0
Interior design					
Upholstery Calypso incl. driver and passenger seat cover ¹¹⁾	_	0	13491	0	0
Upholstery Salerno incl. driver and passenger seat cover ¹¹⁾	_	0	12747	0	0
Furniture layouts					
ISOFIX child seat bracket for third and fourth seat facing direction of travel 10)	_	4	8125	0	0
Makeshift bed	_	4.5	339	0	0
Option to convert single bed to double bed	_	8	1883	_	0
Seating group with harness bench incl. two 3-point harnesses and hook-in and extendable table ⁹⁾	_	29	1951	0	_
Seating group with harness bench incl. two 3-point harnesses and hook-in and extendable table 9)	_	32	1951	_	0
Kitchen					
Room-high compressor refrigerator with separate freezer compartment (131 I)	_	9	13261	0	0
Bathroom					
Shower grate	_	2	1657	0	0
Multimedia					
Second rear view camera in rear moulding	_	1	11541	0	0
Heating					
	_	_			
Diesel hot air heating 6 kW with 1.8 kW electric heating element incl. digital control element and integrated height kit	_	1.3	11585	0	0
Digital control element for hot-air heating	_	0.1	6622	0	0
Air Conditioning					
Roof A/C	_	40	609	0	0
Electrical installation					
2nd Leisure battery Dual Battery System (Lithium), 168 Ah ⁷⁾	_	21.5	13391	0	0
Second leisure battery AGM, 95 Ah ⁷⁾	_	27	830	0	0
Solar power system 100 watt	_	12.6	922	0	0
Water supply					
Insulated waste water tank		8.5	665		0
Insulated waste water tank Insulated waste water tank	_	9	665	0	
model to the trace to the			000		



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for actional equipment change in the model programs. This is a calculated to the contract of the selected optional equipment change in the model programs. This is a calculated to the contract of the selected optional equipment in the model programs. optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and

explanations on the subject of weight can be found in the Legal information section. An increase of load capacity increases the manufacturer-specified mass for optional equipment. The increase results from the higher pay-mass due to the alternative chassis. The increased tare weight of the alternative chassis and, in particular, the weight for any mandatory heavier engine variants (e.g. 180 hp) must be deducted from this. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes. footnotes.

Optional equipment*	Included in package	Additional weight (kg)*	Code	T 15	T 45
Switch for water pump	_	0.2	397	0	0
Packages					
Comfort Package T 15	_	42.3	13804	0	_
Comfort Package T 45	_	48.3	13804	_	0
Package One (awning 3.0m)	_	43.5	14844	0	_
Package One (awning 4.0m)	_	50.5	14844	_	0
Pre-wiring kit	_	5.6	14843	0	0
Winter Comfort Package hot-air heating Globebus Go T 15	_	22.3	13272	0	_
Winter Comfort Package hot-air heating Globebus Go T 45	_	23.8	13272		0
Miscellaneous					
Registration documents (CoC papers)	_	0	15152	*	*

O Optional equipment — Not possible Standard equipment lack Mandatory Δ Not known at the time of publication



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and

explanations on the subject of weight can be found in the Legal information section. An increase of load capacity increases the manufacturer-specified mass for optional equipment. The increase results from the higher pay-mass due to the alternative chassis. The increased tare weight of the alternative chassis and, in particular, the weight for any mandatory heavier engine variants (e.g. 180 hp) must be deducted from this. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes. footnotes.

LEGAL NOTES ON WEIGHT-RELATED INFORMATION

The weight specifications and tests for **motorhomes** are uniformly regulated throughout the EU in EU Implementing Regulation No. 2021/535 (until June 2022: EU Implementing Regulation No. 1230/2012). We have summarised and explained the key terms and legal requirements from this **regulation** for you below. Our **dealers** and the Dethleffs configurator on our website offer you additional assistance in configuring your vehicle.

1. Technically permissible maximum laden mass

The technically permissible maximum laden mass of the vehicle (e.g. 3,500 kg) is a mass specification set by the manufacturer which the vehicle must not exceed. Information on the technically permissible maximum laden mass of the model you have chosen can be found in the technical data. If the vehicle exceeds the technically permissible maximum laden mass in everyday driving, this constitutes an administrative offence which may result in a fine.

2. Mass in running order

In simple terms, the mass in running order is the basic vehicle with standard equipment plus a legally fixed standard weight of 75 kg for the driver. This essentially includes the following items:

- the unladen weight of the vehicle together with the bodywork, including operating fluids such as greases, oils and coolants;
- the **standard equipment**, i.e. all equipment items that are included as standard in the factory-fitted scope of delivery;
- the fresh water tank filled to 100 % in driving mode (driving fill according to manufacturer's specifications;) and an aluminium gas cylinder filled to
- the fuel tank, which is 90 % full, including fuel;
- the driver, whose weight regardless of the actual weight is generally specified as 75 kg in accordance with EU law.

Information on the **mass in running order** can be found for each model in our sales documents. It is important to note that the value for **mass in running order** given in the sales documents is a default value determined in the **type-approval procedure** and verified by the authorities. It is legally permissible and possible for the **mass in running order** of the vehicle delivered to you to deviate from the nominal value stated in the sales documents. The legally permissible **tolerance** is \pm 5 %. In this way, the EU legislator accounts for the fact that certain fluctuations in the **mass in running order** occur due to variations in the weight of supplied parts as well as due to processes and weather conditions.

These weight deviations can be illustrated by means of an example calculation:

- Mass in running order acc. to sales documents: 2,850 kg
- Legally permissible tolerance of ± 5 %: 142.50 kg
- Legally permissible range of **mass in running order**: 2,707.50 kg to 2,992.50 kg

The specific range of permissible weight deviations can be found for each model in the technical data. Dethleffs makes great efforts to reduce weight variations to the minimum that is unavoidable for production reasons. **Deviations** at the upper and lower end of the range are therefore very rare; however, they cannot be completely ruled out technically, even

with all optimisations. The real weight of the vehicle and compliance with the permissible **tolerance** is therefore checked by Dethleffs by weighing each vehicle at the **end of the line**.

3. Mass of the passengers

The **mass of the passengers** is set a standard value of 75 kg for each seat provided by the manufacturer, regardless of the actual weight of the passengers. The **mass of the driver** is already included in the **mass in running order** (see no. 2 above) and is therefore not included again. In the case of a **motorhome** with four **permitted seats**, the **mass of the passengers** is therefore 3 * 75 kg = 225 kg.

4. Optional equipment and actual mass of the vehicle

Optional equipment (also: additional equipment) includes, according to the legal definition, all optional equipment parts not included in the **standard equipment** which are fitted to the vehicle under the responsibility of the manufacturer – i.e. ex works – and can be ordered by the customer (e.g. awning, bicycle or motorbike carrier, satellite system, solar system, oven, etc.). Information on the individual or package weights of the **optional equipment** that can be ordered can be found in our sales documents. **Optional equipment** in this sense does not include other **accessories** that are retrofitted by the **dealer** or you personally after the vehicle has been delivered ex works.

The mass of the vehicle in running order (see no. 2 above) and the mass of the optional equipment fitted to a specific vehicle at the factory are together referred to as the actual mass. You will find the corresponding information for your vehicle after handover under item 13.2 of the Certificate of Conformity (CoC). Please note that this specification also represents a standardised value. Since the mass in running order – as an element of the actual mass – is subject to a legally permissible tolerance of $\pm~5~\%$ (see no. 2), the actual mass may also deviate accordingly from the stated nominal value.

5. Pay-mass and minimum pay-mass

The installation of optional equipment is also subject to technical and legal limits: Only so much optional equipment can be ordered and fitted at the factory that sufficient free weight remains for baggage and other accessories ("pay-mass") without exceeding the technically permissible maximum laden mass. The pay-mass is calculated by subtracting the mass in running order (nominal value according to sales documents, see no. 2 above), mass of the optional equipment and the mass of the passengers (see no. 3 above) from the technically permissible maximum laden mass (see no. 1 above). The EU regulations stipulate a fixed minimum pay-mass for motorhomes, which must remain as a minimum for baggage or other non-factory-fitted accessories. This minimum pay-mass is calculated as follows:

Minimum pay-mass in kg ≥ 10 * (n + L)

Where: "n" is the maximum number of passengers plus the driver and "L" is the overall length of the vehicle in metres.

For a motorhome with a length of 6 m and 4 approved seats, the minimum pay-mass is therefore e.g. 10 kg * (4 + 6) = 100 kg.

To ensure that the minimum pay-mass is maintained, there is a maximum combination of optional equipment that can be ordered for each vehicle model. In the above example with a minimum pay-mass of 100 kg, the total mass of optional equipment for a vehicle with four permitted seats and a mass in running order of 2,850 kg should not exceed 325 kg:

3,500 kg technically permissible maximum laden mass

- 2,850 kg mass in running order
 - 3*75 kg mass of the passengers
 - 100 kg minimum pay-mass

325 kg maximum permissible mass of optional equipment

It is important to note that this calculation is based on the default value for mass in running order as defined in the type-approval procedure, without taking into account the permissible weight deviations for mass in running order (see no. 2 above). If the maximum permissible value for the optional equipment of (in the example) 325 kg is almost or completely exhausted, an upward weight deviation can therefore result in the minimum pay-mass of 100 kg being met mathematically using the default value for the mass in running order, although in fact there is no corresponding load capacity. Here, too, an example calculation for a vehicle with four seats, whose real weighed mass in running order is 2 % above the nominal value:

3.500 kg technically permissible maximum laden mass
- 2.907 kg real weighed mass in running order (+ 2 % compared to the stated value of 2,850 kg)
- 3*75 kg mass of the passengers

- 325 kg optional equipment (maximum permissible value) = 43 kg actual load capacity (< minimum pay-mass of 100 kg)

In order to avoid such a situation, Dethleffs further reduces the maximum permissible weight of the total **optional equipment** that can be ordered on a model-specific basis. The limitation of **optional equipment** is intended to ensure that the **minimum pay-mass**, i.e. the legally prescribed free mass for **baggage** and retrofitted **accessories**, is actually available for the **vehicle load capacity** of the vehicles delivered by Dethleffs. Since the weight of a specific vehicle can only be determined when it is weighed at the **end of the line**, in very rare cases a situation may arise in which the **minimum pay-mass** at the **end of the line** is not guaranteed, despite this limitation of **optional equipment**. In order to guarantee the **minimum pay-mass** even in these cases, Dethleffs will check together with your **trade partner** and you before delivery of the vehicle whether, for example, the vehicle is loaded up, seats are reduced or **optional equipment** is removed.

6. Effects of tolerances of the mass in running order on the pay-mass

Regardless of the minimum pay-mass, you should note that unavoidable production-related fluctuations in the mass in running order – both upwards and downwards – have a mirror-image effect on the remaining load capacity: If you order our example vehicle (see no. 3. above), for example, with optional equipment with a total weight of 150 kg, the calculated pay-mass based on the default value for the mass in running order is 275 kg. The load capacity actually available may deviate from this value due to tolerances and may be higher or lower. If the mass in running or-

der of your vehicle is, for example, permissibly 2 % higher than stated in the sales documents, the **load capacity** is reduced from 275 kg to 218 kg:

3.500 kg technically permissible maximum laden mass

2.907 kg $\,$ real weighed mass in running order (+ 2 % compared to the

stated value of 2,850 kg) 3*75 kg mass of the passengers

150 kg **optional equipment** ordered for the specific vehicle

= 218 kg sactual load capacity

As a precaution to ensure that the calculated pay-mass is actually given, you should therefore take the possible and permissible tolerances for the mass in running order into account when configuring your vehicle. We also recommend that you weigh the laden motorhome on a non-automatic scale before each journey and, taking the individual weight of the passengers into account, determine whether the technically permissible maximum laden mass and the technically permissible maximum mass on the axle are observed.