## Trend Low Profile



The bestseller in the Dethleffs model programme has been completely revised: Modern design, extensive standard equipment and practical new functions make the Trend the undisputed price/performance winner. A special comfort feature is the stepless IsoProtect living area floor, which extends from the driver's cabin to the bathroom. As a Low Profile model, the Trend has an opening window in the driver's cab bonnet as standard, for an airy, light-flooded interior.

Technical info	
Overall length, approx.	671 - 741 cm
Overall width, approx.	233 cm
Overall height, approx.	300 cm
Headroom in living area, approx.	205 cm

Maximum values partly not possible for all models or only in connection with certain options.

## Upholstery







+ Upholstery Yoko



+ Upholstery Heron (partial textileleather) O

### Plus factors

- + Lifetime Smart superstructure with wood-free, GRPclad underbody
- + Aerodynamic T-hood with pop-up window as standard
- + Exclusive rear design with top-entry rear wall, ShapeLine LED tail lights and 3rd brake light integrated into the rear spoiler
- + Large rear garage can be loaded on both sides, onehand operation of the garage doors, lighting, 230 V socket and sturdy lashing rails
- + 70 cm wide habitation door with convenient coupe entrance
- + Level Iso-Protect comfort flooring in the living area without landings or steps
- + New overhead locker concept with handleless fronts and large storage volume incl. AirPlus overhead locker rear ventilation
- + Sleeping area: Outstanding sleeping comfort with 150 mm thick Evopore cold foam mattresses

## Wood décor



+ Wood décor Ashton

O optionally available

















# Trend Low Profile Technical info







Trend Low Profile		T 6617 EB	T 6817 EB	Т 6877
Standard chassis		Fiat Ducato Light Low Platform	Fiat Ducato Light Low Platform	Fiat Ducato Light Low Platform
Emission standards		Euro 6e	Euro 6e	Euro 6e
Overall length, approx.	cm	671	699	699
Overall width, approx.	cm	233	233	233
Overall height, approx.	cm	300 1)	300 1)	300 1)
Headroom in living area, approx.	cm	205	205	205
Towable load braked/unbraked	kg	2000 / 750	2000 / 750	2000 / 750
Wheelbase, approx.	mm	3800	3800	3800
Bed dimension: Front bed, L x W, approx.	cm	198 x 88 🔿	198 x 140 - 112 O	198 x 140 O
Bed dimension: Central / middle bed, L X W, approx.	cm	155 x 100 - 80 O	206 x 100 - 65 O	210 x 118 - 80 O
Bed dimension: Rear bed, L x W, approx.	cm	212 x 80 / 201 x 80 / 211 x 144 O	207 x 80 / 194 x 80 / 211 x 192 O	212 x 162
Sleeping berths standard / max.		2/40	2/50	2/50
Standard engine		140 MultiJet 3	140 MultiJet 3	140 MultiJet 3
kW (bhp)		103 (140)	103 (140)	103 (140)
Mass in running order (+/-5%)*	kg	2780 (2641 to 2919)*	2820 (2679 to 2961)*	2850 (2708 to 2993)*
Manufacturer-specified mass for optional equipment*	kg	387	344	314
Technically permissible maximum laden mass*	kg	3499	3499	3499
Permitted number of seats (including driver)*		4	4	4 - 5 🔿
Refrigerator volume (thereof freezer), approx.	I	137 (15)	137 (15)	137 (15)
Waste water tank, approx.	1	90	90	90
Fresh water tank capacity, total/ Fresh water tank capacity at driving filling	g I	116 / 20	116 / 20	116 / 20
Measurement storage opening left (W x H)	cm	40 x 75 O / 40 x 110	85 x 65 O / 85 x 110	85 x 110
Measurement storage opening right (W x H)	cm	75 x 75 🔾 / 75 x 110	85 x 65 O / 85 x 110	85 x 110



The specified mass in running order is a default value defined in the type-approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to  $\pm$  5 % of the mass in running order are legally permissible and possible. The permissible range in kilograms is given in brackets after the mass in running order. The manufacturer-specified mass for optional equipment is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. The limitation of optional equipment is intended to ensure that the minimum pay-mass, i.e. the legally prescribed free mass for baggage and retrofitted accessories, is actually available for the vehicle load capacity of the vehicles delivered by Dethleffs. The real weight of your vehicle ex works can only be determined when it is

weighed at the end of the line. If, in exceptional cases, the weighing shows that the actual load capacity falls below theminimum pay-mass despite limiting the optional equipment due to a permissible weight deviation, we will check together with your trade partner and you whether we should, for example, increase the load capacity of the vehicle, reduce the number of seats or remove optional equipment before delivering the vehicle. The technically permissible maximum laden mass of the vehicle and the technically permissible maximum mass on the axle must not be exceeded. Detailed information & explanations on the subject of weight and the configuration of the vehicle can be found in the section Legal information. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes.

# Trend Low Profile Technical info







Trend Low Profile		T 7057 EB	T 7057 DBL	T 7057 EBL
Standard chassis		Fiat Ducato Light Low Platform	Fiat Ducato Light Low Platform	Fiat Ducato Light Low Platform
Emission standards		Euro 6e	Euro 6e	Euro 6e
Overall length, approx.	cm	741	741	741
Overall width, approx.	cm	233	233	233
Overall height, approx.	cm	300 1)	300 1)	300 1)
Headroom in living area, approx.	cm	205	205 205	
Towable load braked/unbraked	kg	2000 / 750	2000 / 750	2000 / 750
Wheelbase, approx.	mm	4035	4035	4035
Bed dimension: Front bed, L x W, approx.	cm	198 x 140 - 120 O	198 x 140 O	198 x 140 🔾
Bed dimension: Central / middle bed, L X W, approx.	cm	210 x 118 - 80 O	206 x 110 - 88 O	206 x 110 - 88 O
Bed dimension: Rear bed, L x W, approx.	cm	214 x 80 / 212 x 80 / 211 x 201 O	195 x 150	211 x 80 / 207 x 80 / 211 x 198 O
Sleeping berths standard / max.		2/50	2/50	2/50
Standard engine		140 MultiJet 3	140 MultiJet 3	140 MultiJet 3
kW (bhp)		103 (140)	103 (140)	103 (140)
Mass in running order (+/-5%)*	kg	2900 (2755 to 3045)*	2940 (2793 to 3087)*	2940 (2793 to 3087)*
Manufacturer-specified mass for optional equipment*	kg	260	220	220
Technically permissible maximum laden mass*	kg	3499	3499	3499
Permitted number of seats (including driver)*		4 - 5 🔾	4	4
Refrigerator volume (thereof freezer), approx.	1	137 (15) / 137 (15) O	137 (15) / 137 (15) 🔿	137 (15) / 137 (15) O
Waste water tank, approx.	- 1	90	90	90
Fresh water tank capacity, total/ Fresh water tank capacity at driving filling	]	116 / 20	116 / 20	116 / 20
Measurement storage opening left (W x H)	cm	90 x 75 O / 90 x 110	90 x 110	90 x 75 O / 90 x 110
Measurement storage opening right (W x H)	cm	90 x 75 O / 90 x 110	90 x 110	90 x 75 O / 90 x 110

O Optional equipment — Not possible ● Standard equipment ◆ Mandatory △ Not known at the time of publication



The specified mass in running order is a default value defined in the type-approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to  $\pm$  5 % of the mass in running order are legally permissible and possible. The permissible range in kilograms is given in brackets after the mass in running order. The manufacturer-specified mass for optional equipment is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. The limitation of optional equipment is intended to ensure that the minimum pay-mass, i.e. the legally prescribed free mass for baggage and retrofitted accessories, is actually available for the vehicle load capacity of the vehicles delivered by Dethleffs. The real weight of your vehicle ex works can only be determined when it is

weighed at the end of the line. If, in exceptional cases, the weighing shows that the actual load capacity falls below theminimum pay-mass despite limiting the optional equipment due to a permissible weight deviation, we will check together with your trade partner and you whether we should, for example, increase the load capacity of the vehicle, reduce the number of seats or remove optional equipment before delivering the vehicle. The technically permissible maximum laden mass of the vehicle and the technically permissible maximum mass on the axle must not be exceeded. Detailed information & explanations on the subject of weight and the configuration of the vehicle can be found in the section Legal information. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes.

Solity wheel I int is 6"  Field Decision Light Bow platform (2.199 kg), Multiglet 140 (2.21 / 103 kW / 140 lpp), 6-speed memoril transmission  80	Standard equipment	T 6617 EB	T 6817 EB	T 6877	T 7057 EB	T 7057 DBL	T 7057 EBL
Tiest Chansatis feet Uruse  Tiest Chansatis Ashabitis system / I film (electronic brakeforce distribution)  Anti- that flad device  Adultment & Bobke Assolit after a collision  Coptain seats for direct and front passenger, swived function  Coptain seats for direct and front passenger, swived function  Coptain seats for direct and front passenger, swived function  Coptain seats for direct of the destibuted  Cop Indicate the seat of the destibuted  Cop Indicate the seat of the destibuted  Cop Indicate the seat of the destibuted	1111 1111						
ABS (anti-tack bracking system) / EBD (electronic brakeforce distribution)  ABS (anti-tack device)  Authoristic brack assist after a collision  Quarti-field device  Authoristic Brack Assist after a collision  Crosswand Assist  Crosswand Assist  Crosswand Assist  Crosswand Assist  Crosswand Assist  Crosswand Assist  Crosswand In the centre of the distributed with the control of the control of the distributed with the control of the distributed with administration minore  DAB+ radia antenna integrated into right exterior minore  Daystime ranning lights integrated into headilights  Devices Inan Possenger airbags  Driver and Driver				•	•	•	•
ABS (anti-lock braking system) / EBD (electronic brakelorce distribution)  Auti-their device  Auti-their device Assist after a collision  Capitalis seals for differ and front passenge, swivel function  Capitalis seals for differ and front passenge, swivel function  Capitalis seals for differ and front passenge, swivel function  Capitalis seals for differ and front passenge, swivel function  Capitalis seals for differ and front passenge, swivel function  Capitalis seals for differ and front passenge, swivel function  Capitalis seals for differ and front passenge and seals for differ and front passenge and seals are also for differ and passenge althoughts  Diver and passenge defection  Diver's can in manual A/C  Spirit and Auti-their function front and integrated turn indicator  Electrically adjustable and heated exterior mirrors incl. blind spot mirror and integrated turn indicator  Electrical passenge althoughts swite  For glights and L. cornering light  For all their device  Auti-their for their passenge althoughts swite  For glights ind. cornering light  For all their device  Auti-their device  Auti-their device  Auti-their device and passenge are seat  Auti-their scholarity advised and passenge seat  Auti-their scholarity and their device and passenger seat  Auti-their device and passenge are seat  Auti-their scholarity and their device and passenger seat  Auti-their scholarity and their scholarity and their device and passenger							
Abt-ther't device Abstituted from Assist after a collision  Applain seasts for driver and front passenger, swivel function  Crosswind Assist  Crosswind Assist  Crosswind Assist  Crosswind Assist  Cups broker in the centre of the dashboard  Cup broker in the centre of the centr	Fiat chassis features						
Automatic Brake Assist after a collision  Applian seats for driver and front possenger, swivel function  Crossword Assist  Crubse control  Que holder in the centre of the disabboard  ABE- radio anterona integrated into right exterior mirror  Doshboard with aluminism application  Doylinne running lights integrated into headilights  Disciplinated So like incl. 19t. Addibus tank  Doviner and passenger distection  Driver and passenger distection and death and passenger seat  Driver and passenger distection and passenger seat  Driv	ABS (anti-lock braking system) / EBD (electronic brakeforce distribution)	•					
Captain seats for driver and front passenger, servicel functions  Crosswind Assist  Crosswind Assist  Crosswind Assist  Crosswond Assist	Anti-theft device	•	•	•	•	•	•
Cross-control  Crup Holder in the centre of the dishboard  OAB+ radio antenna integrated into light exterior minro  Soabbeard with Jammium application  Doytime running lights integrated into headlights  Oise I land, 19 liter int. 19 A ridblie bank  Divers and passenger detection  Drivers and passenger detection minros incl. blind spot minror and integrated turn indicator  Driver and passenger detection  Drivers and passenger detection minros incl. blind spot minror and integrated turn indicator  Drivers and passenger detection and double armests for driver and passenger seat  Driver and passenger detection and double armests for driver and passenger seat  Driver and this dijustment and double armests for driver and passenger seat  Driver and basenger drivers and double armests for driver and passenger seat  Driver and basenger drivers and double armests for driver and passenger seat  Driver and basenger drivers and double armests for driver and passenger seat  Driver and basenger and basenger and double armests for driver and passenger seat	Automatic Brake Assist after a collision						
Cruse control  (up holder in the centre of the dashboard  (up holder in the centre of the		•	•	•	•	•	•
Cup holder in the centre of the dischboard  OAB's radio antenna integrated into right exterior mirror  OAB's radio antenna integrated into right exterior mirror  OAP's radio antenna integrated into headlights  Oavytime running lights integrated into headlights  Oriver and passenger airbags  Oriver and passenger discass  Orivers and passenger discass  Oriver and passenger discass while a control of the contro							
DASP - radio antenna integrated into right exterior mirror  Das bloard with aluminium application  Das bloard with aluminium application  Das bloard with aluminium application  Diesel tank 90 little ind. 1914. Addibut tank  Direct and passenger airbags  Driver and passenger airbags  Driver and passenger of election  Direct you be manual A/C  Self ind. ASP, Tacriton Plus, Hill Holder and Hill Descent Control  Electrically adjustable and heated exterior mirrors incl. blind spot mirror and integrated turn indicator  Exterior colour chassis white  Fool in John Francis Plus, Hill Holder and Hill Descent Control  Electrically adjustable and heated exterior mirrors incl. blind spot mirror and integrated turn indicator  Exterior colour chassis white  Fool in John Francis Plus Hill Holder and Hill Descent Control  Electrically adjustable and heated exterior mirrors incl. blind spot mirror and integrated turn indicator  Exterior colour chassis white  Fool is played in Concerning light  Fool where the spoting		•				•	
Dashbaard with aluminum application Day-time running lights integrated into headilghts Driver and passenger detection Driver's cab manual A/C SEP inct. ASR, Traction Plus, Alli Holder and Hill Descent Control Leictrically adjustable and heated exterior mirrors incl. blind spot mirror and integrated turn indicator Exterior colour chassis white Fog lights ind. comering light Front wheel driver GEP lightwelphit leaf spring Height and tilt adjustment and double ammests for driver and passenger seat Leather steering wheel and speak nobe withleather sleeve Peadded double ammests, fabric cover Peadded double ammest of the driver's cabin Steering wheel with control elements  To cover the pead of the driver's cabin Steering wheel with control element	·						
Daytime running lights integrated into headlights  Oiseal tank 90 line ind. 1914. Addituct tank  Oiver and passenger adhases  Orivers and passenger and passenger adhases  Orivers and passenger and			•	•	•	•	•
Diesel tank 90 litre incl. 19I AdBlue tank  Driver and passenger aibags  Driver and passenger detection  Driver's cab manual A/C  SEP Incl. ASR, Traction Plus, Hill Holder and Hill Descent Control  Electrically adjustable and heated exterior mirrors incl. blind spot mirror and integrated turn indicator  Exterior colour chassis white  Fog lights incl. comening light  For colour chassis white  Fog lights incl. comening light  For colour chassis white  Fog lights incl. comening light  For colour chassis white  Fog lights incl. comening light  For colour chassis white  Fog lights incl. comening light  For colour chassis white  Fog lights incl. comening light  For colour chassis white  Fog lights incl. comening light  For colour chassis white  Fog lights incl. comening light  For colour chassis white  Fog lights incl. comening light  For colour chassis white  For colou							
Driver and passenger airbags Driver and passenger detection Drivers can branast AC ESP Incl. ASR, Traction Plus, Hill Holder and Hill Descent Control Electrically adjustable and heated exterior mirrors incl. blind spot mirror and integrated turn indicator Electrically adjustable and heated exterior mirrors incl. blind spot mirror and integrated turn indicator Electrically adjustable and heated exterior mirrors incl. blind spot mirror and integrated turn indicator Front-whole drive Front-whole drive Elegiblith spot and titl adjustment and double armests for driver and passenger seat Elegiblith spot and titl adjustment and double armests for driver and passenger seat Leather steering wheel and gear knob writhleather sleeve Painted front bumper in body colour incl. black skid plate Preparation for radio system incl. loudspeakers in the driver's cabin Steering wheel with control elements Trailer Stability Assist Progration for radio system incl. loudspeakers in the driver's cabin Steering wheel with control elements Trailer Stability Assist Progration for radio system incl. loudspeakers in the driver's cabin Steering wheel with control elements Trailer Stability Assist Progration for radio system incl. loudspeakers in the driver's cabin Steering wheel with control elements Trailer Stability Assist Progration for radio system incl. loudspeakers in the driver's cabin Steering wheel with control elements Trailer Stability Assist Progration for radio system incl. loudspeakers in the driver's cabin Steering wheel with control elements Trailer Stability Assist Progration for radio system incl. loudspeakers in the driver's cabin Steering wheel white control elements Trailer Stability Assist Progration for radio system incl. loudspeakers in the driver's cabin Steering wheel and towning eye Writter tyres Mr. Scamping (with snowflake)  Progration for radio system incl. loudspeakers in the driver's cabin Steering wheel and towning eye Writter tyres Mr. Scamping (with snowflake)  Progration for radio system incl. loudspeakers							
Driver's can branual A/C  Electrically adjustable and heated exterior mirrors incl. blind spot mirror and integrated turn indicator  Exterior colour chassis white  Driven's colour chassis wh							
Driver's cab manual A/C  SPS incl. ASS, Traction Plus, Hill Holder and Hill Descent Control  Exterior colour chassis white  Fog lights incl. cornering light  For incrt wheel drive  GRP lightweight leaf spring  Height and tilt adjustment and double armests for driver and passenger seat  Leather steering wheel and gear knob withleather sleeve  Padded double armiests, fabric cover  Padded double armiests for driver and passenger seat  Leather steering wheel and gear know withleather sleeve  Padded double armiests, fabric cover  Padded double armiests, fabric cover  Padded double armiests for driver and passenger seat  Padded double armiests fabric and tild filt and tilt fabric and tilt and tilt fabric and tilt and tilt fabric and tilt and tilt fabri							
Electrically adjustable and heated exterior mirrors incl. blind spot mirror and integrated turn indicator  checkrically adjustable and heated exterior mirrors incl. blind spot mirror and integrated turn indicator  checkrically adjustable and heated exterior mirrors incl. blind spot mirror and integrated turn indicator  checkrically adjustable and heated exterior mirrors incl. blind spot mirror and integrated turn indicator  checkrically adjustable and heated exterior mirrors incl. blind spot mirror and integrated turn indicator  checkrically adjustable and heated exterior mirrors incl. blind spot mirror and integrated turn indicator  checkrically adjustable and heated exterior mirrors incl. blind spot mirror and integrated turn indicator  checkrically adjustable and heated exterior mirrors incl. blind spot mirror and integrated turn indicator  checkrically adjustable and heated exterior mirrors incl. blind spot mirror and integrated turn indicator  checkrically adjustable and heated exterior mirrors incl. blind spot mirror and integrated under an and the double armrests, fabric cover and peak exterior features  checkrically adjustable and peak know with leathers spot mirror and integrated in rear spoiler and retracted rear wall  checkrically adjustable and the spot mirror and integrated in rear spoiler and retracted rear wall  checkrically adjustable and the spot mirror and integrated in rear spoiler and retracted rear wall  checkrically adjustable and the spot mirror and integrated in rear spoiler and retracted rear wall  checkrically adjustable and the spot mirror and integrated in rear spoiler and retracted rear wall  checkrically adjustable and the spot mirror and integrated in rear spoiler and retracted rear wall  checkrically adjustable and the spot mirror and integrated in rear spoiler and retracted rear wall  checkrically adjustable and the spot mirror and spot							
Electrically adjustable and heated exterior mirrors incl. blind spot mirror and integrated turn indicator  Exterior colour chassis white  Front-wheel drive  GRP lightweight leaf spring  Height and tilt adjustment and double armrests for driver and passenger seat  Leather steering wheel and gear knob withleather sleeve  Padded double armrests, fabric cover  Padded for radio system incl. loudspeakers in the driver's cabin  Steering wheel with control elements  Trailer Stability Assist  Winder tyres M+S Camping (with snowflake)  Patrior features  Betterior reatures  Betterior reatures  Betterior destine  Betterior de							
Exterior colour chassis white  Fog lights incl. conering light  For Contributed live  GRP lightweight leaf spring  GRP lightweight leaf spring  Leather steering wheel and gear knob withleather sleeve  And till adjustment and double armrests for driver and passenger seat  Leather steering wheel and gear knob withleather sleeve  Painted front bumper in body colour incl. black skid plate  Preparation for radio system incl. loudspeakers in the driver's cabin  Steering wheel with control elements  Trailer Stability Assist  Trailer Stability Assist  Trailer Stability Assist  Trailer Stability Assist  Widened rear aske  Widened rear aske  Widened rear aske  Widened rear aske  Bethelf's Exclusive rear light carrier with Shapetine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  70 cm wide habitation door  Betforom window right and left  EPS insulation  First press Protect comfort floor in the living area without landings  Floor thickness- 49 mm, side wall thickness- 34mm and roof thickness- 35 mm  Flyscreen habitation access with comfortable coupe entrance  Habitation access with comfortable coupe entrance  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Opening window in T-hood  Panorama skylight 70 x 50 cm in the living area  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1, 12 x 20 y socket  Exterior design							
Frog lights incl. cornering light From twheel drive From the dight and tilt adjustment and double armrests for driver and passenger seat Leather steering wheel and gear knob withleather sleeve Padded double armrests, fabric cover Propriet in body colour incl. black skid plate Preparation for radio system incl. Loudspeakers in the driver's cabin  Steering wheel with control elements  From two deal and towing eye Widened rear axle Winter tyres M+S Camping (with snowflake)  **Exterior features**  **Exterior design**  **Dethelf's Exclusive rear light carrier with ShapeLine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  **Open the structure of t				•	•		
Front-wheel drive  GRP lightweight leaf spring  Height and tilt adjustment and double armrests for driver and passenger seat  Leather steering wheel and gear knob withleather sleeve  Padded double armrests, fabric cover  Painted front bumper in body colour incl. black skid plate  Preparation for radio system incl. loudspeakers in the driver's cabin  Steering wheel with control elements  Trailer stability Assist  Trailer stability Assist  Trailer stability Assist  Windened rear axle  Winter tyres M-S Camping (with snowflake)  Exterior features  Dethleffs Exclusive rear light carrier with Shapetine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  70 cm wide habitation door  Bedroom window right and left  PPS insulation  Even Iso-Protect comfort floor in the living area without landings  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Popening window in T-hood  Ponorama skylight 70 x 50 cm in the living area  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1 x 230 V socket  Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface  Exterior design		•		•		•	•
Height and tilt adjustment and double armrests for driver and passenger seat  Leather steering wheel and gear knob withleather sleeve  Painted front bumper in body colour incl. black skid plate Preparation for radio system incl. loudspeakers in the driver's cabin  Steering wheel with control elements Trailer Stability Assist Tyre inflation kit and towing eye Widened rear axle Widened rear axle Winter tyres M+S Camping (with snowflake)  Exterior features  Debthelfs Exclusive rear light carrier with Shapetine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall 70 cm wide habitation door  Bedroom window right and left PSP insulation Fens in the living area without landings Hoor thickness: 49 mm, side wall thickness: 34 mm and roof thickness: 35 mm Flyscreen habitation door  GRP roof Habitation access with comfortable coupe entrance Habitation access with comfortable, wide, electric step Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof Opening window in T-hood Panorama skylight 70 x 50 cm in the living area Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, lilluminated, 1 x 230 v socket  Exterior design	Front-wheel drive		•	•	•	•	•
Height and tilt adjustment and double armrests for driver and passenger seat  Leather steering wheel and gear knob withleather sleeve  Painted front bumper in body colour incl. black skid plate Preparation for radio system incl. loudspeakers in the driver's cabin  Steering wheel with control elements Trailer Stability Assist Tyre inflation kit and towing eye Widened rear axle Widened rear axle Winter tyres M+S Camping (with snowflake)  Exterior features  Debthelfs Exclusive rear light carrier with Shapetine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall 70 cm wide habitation door  Bedroom window right and left PSP insulation Fens in the living area without landings Hoor thickness: 49 mm, side wall thickness: 34 mm and roof thickness: 35 mm Flyscreen habitation door  GRP roof Habitation access with comfortable coupe entrance Habitation access with comfortable, wide, electric step Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof Opening window in T-hood Panorama skylight 70 x 50 cm in the living area Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, lilluminated, 1 x 230 v socket  Exterior design		•	•	•	•	•	•
Leather steering wheel and gear knob withleather sleeve  Padded double armrests, fabric cover  Padded double armrests, fabric cover  Preparation from tournper in body colour incl. black skid plate  Preparation for radio system incl. loudspeakers in the driver's cabin  Steering wheel with control elements  Steering wheel with control elements  Trailer Stability Assist  Tyre inflation kit and towing eye  Wither tyres Air-S Camping (with snowflake)  Exterior features  Dethleffs Exclusive rear light carrier with ShapeLine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  To cm wide habitation door  Bedroom window right and left  EPS insulation  Fiven Iso-Protect comfort floor in the living area without landings  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  Bedroom window right and left  EPS insulation oor  Bedroom window right and left  EPS insulation oor  EVEN Iso-Protect comfort floor in the living area without landings  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Plyscreen habitation door  Bedroom window in T-hood  Alabitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Opening window in T-hood  Panorama skylight 70 x 50 cm in the living area  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1 x 230 V socket  Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface  Exterior design							
Preparation for radio system incl. loudspeakers in the driver's cabin  Steering wheel with control elements Tryie inflation kit and towing eye Widened rear axle Winter tyres M+S Camping (with snowflake)  Exterior features  Dethleffs Exclusive rear light carrier with Shapetine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall or or middle habitation door  Bedroom window right and left EPS insulation  Even Iso-Protect comfort floor in the living area without landings Floor thickness: 49 mm, side wall thickness: 34 mm and roof thickness: 35 mm Flyscreen habitation door  GRP roof Habitation access with comfortable coupe entrance Habitation access with comfortable, wide, electric step Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Opening window in T-hood Panorama skylight 70 x 50 cm in the living area Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1 x 230 Y socket Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface  Exterior design	Leather steering wheel and gear knob withleather sleeve	•	•	•	•	•	•
Preparation for radio system incl. loudspeakers in the driver's cabin  Steering wheel with control elements  Trailer Stability Assist  Tyre inflation kit and towing eye  Winter tyres M-5 Camping (with snowflake)  Exterior features  Dethleffs Exclusive rear light carrier with Shapetine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  70 cm wide habitation door  Bedroom window right and left  EPS insulation  Even Iso-Protect comfort floor in the living area without landings  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Opening window in T-hood  Panorama skylight 70 x 50 cm in the living area  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1 x 230 V socket  Exterior design	Padded double armrests, fabric cover			•		•	
Steering wheel with control elements  Trailer Stability Assist  Type inflation kit and towing eye  Widened rear axle  Widened rear axle  Widened rear axle  Exterior features  Dethleffs Exclusive rear light carrier with Shapetine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  70 cm wide habitation door  Bedroom window right and left  EPS insulation  EVEN ISO-Protect comfort floor in the living area without landings  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Depening window in T-hood  Penorama skylight 70 x 50 cm in the living area  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1 x 230 V socket  Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface  Exterior design	Painted front bumper in body colour incl. black skid plate	•	•	•	•	•	•
Trailer Stability Assist  Tyre inflation kit and towing eye  Widened rear axle  Winter tyres M+S Camping (with snowflake)  Exterior features  Dethleffs Exclusive rear light carrier with Shapetine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  70 cm wide habitation door  80 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Preparation for radio system incl. loudspeakers in the driver's cabin					•	•
Widened rear axle Winter tyres M+S Camping (with snowflake)  Exterior features  Dethleffs Exclusive rear light carrier with Shapetine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall 70 cm wide habitation door  Bedroom window right and left EYPS insulation EXPS insula	Steering wheel with control elements	•					
Winter tyres M+S Camping (with snowflake)  Exterior features  Dethleffs Exclusive rear light carrier with ShapeLine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall 70 cm wide habitation door  Bedroom window right and left  EPS insulation  EPS insulation  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof coof  Panorama skylight 70 x 50 cm in the living area  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1 x 230 V socket  Exterior design	Trailer Stability Assist	•					
Winter tyres M+5 Camping (with snowflake)  Exterior features  Dethleffs Exclusive rear light carrier with Shapetine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  70 cm wide habitation door  Bedroom window right and left  EPS insulation  Even Iso-Protect comfort floor in the living area without landings  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Opening window in T-hood  Panorama skylight 70 x 50 cm in the living area  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1 x 230 V socket  Exterior design	Tyre inflation kit and towing eye	•	•	•	•	•	•
Dethleffs Exclusive rear light carrier with ShapeLine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  70 cm wide habitation door  8edroom window right and left  EPS insulation  Even Iso-Protect comfort floor in the living area without landings  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  6RP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panorama skylight 70 x 50 cm in the living area  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1 x 230 V socket  Exterior design	Widened rear axle						
Dethleffs Exclusive rear light carrier with ShapeLine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  70 cm wide habitation door  Bedroom window right and left  EPS insulation  Even Iso-Protect comfort floor in the living area without landings  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Opening window in T-hood  Panorama skylight 70 x 50 cm in the living area  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1 x 230 V socket  Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface  Exterior design	Winter tyres M+S Camping (with snowflake)	•	•	•	•	•	•
Bedroom window right and left  EVEN Isoulation  EVEN Isoulation  EVEN Isoulation  EVEN Isoulation  EVEN Isoulation  EVEN Isour thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRR Proof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Opening window in T-hood  Panorama skylight 70 x 50 cm in the living area  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1 x 230 V socket  EXECUTED IN THE INVENTIGATION OF THE INVENTIGATION O	Exterior features						
Bedroom window right and left  EPS insulation  Even Iso-Protect comfort floor in the living area without landings  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Opening window in T-hood  Panorama skylight 70 x 50 cm in the living area  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1 x 230 V socket  Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface  Exterior design	Dethleffs Exclusive rear light carrier with ShapeLine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall	•	•	•	•	•	•
Even Iso-Protect comfort floor in the living area without landings  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Opening window in T-hood  Panorama skylight 70 x 50 cm in the living area  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1 x 230 V socket  Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface  Exterior design	70 cm wide habitation door						•
Even Iso-Protect comfort floor in the living area without landings  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Opening window in T-hood  Panorama skylight 70 x 50 cm in the living area  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1 x 230 V socket  Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface  Exterior design	Bedroom window right and left	•	•	•	•	•	•
Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Opening window in T-hood  Panorama skylight 70 x 50 cm in the living area  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1 x 230 V socket  Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface  Exterior design	EPS insulation	•					•
Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Opening window in T-hood  Panorama skylight 70 x 50 cm in the living area  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1 x 230 V socket  Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface  Exterior design	Even Iso-Protect comfort floor in the living area without landings	•	•	•	•	•	•
Habitation access with comfortable coupe entrance Habitation access with comfortable, wide, electric step Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof Opening window in T-hood Panorama skylight 70 x 50 cm in the living area Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1 x 230 V socket Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface  Exterior design	Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm						
Habitation access with comfortable coupe entrance Habitation access with comfortable, wide, electric step  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Opening window in T-hood  Panorama skylight 70 x 50 cm in the living area  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1 x 230 V socket  Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface  Exterior design	Flyscreen habitation door	•	•	•	•	•	•
Habitation access with comfortable, wide, electric step  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Opening window in T-hood  Panorama skylight 70 x 50 cm in the living area  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1 x 230 V socket  Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface	GRP roof						
Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Opening window in T-hood  Panorama skylight 70 x 50 cm in the living area  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1 x 230 V socket  Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface		•	•	•	•	•	•
Opening window in T-hood  Panorama skylight 70 x 50 cm in the living area  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1 x 230 V socket  Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface  Exterior design	Habitation access with comfortable, wide, electric step						
Panorama skylight 70 x 50 cm in the living area  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1 x 230 V socket  Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface  Exterior design	roof	•	•	•	•	•	•
Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1 x 230 V socket  Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface  Exterior design	Opening window in T-hood						
illuminated, 1 x 230 V socket  Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface  Exterior design	Panorama skylight 70 x 50 cm in the living area	•	•	•	•	•	•
Exterior design	Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails, illuminated, 1 x 230 V socket	•	•	•	•	•	•
	Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface	•	•	•	•	•	•
Exterior body painted in white	Exterior design						
	Exterior body painted in white	•	•	•	•	•	•

Standard equipment	T 6617 EB	T 6817 EB	T 6877	T 7057 EB	T 7057 DBL	T 7057 EBL
Interior design						
Upholstery Saros	•	•	•	•	•	•
Wood décor Ashton		•	•	•	•	•
Textile equipment						
Rear beds with ergonomic wooden slatted frames and 150 mm thick 7-zone premium mattresses made of climate-regulating material	•	•	•	•	•	•
Furniture layouts						
AirPlus overhead locker rear ventilation to avoid condensation	•	•	•	•	•	•
Comfortable lounge seating group with 2 folding seats incl. 3-point belts incl. Isofix and free-standing, rigid table base	_	_	_	_	•	•
Double bed high in the rear, transverse	_	_		_	-	_
Floor-to-ceiling closet with pull-out step for convenient access to the bed	_	_	•	_	_	_
Floor-to-ceiling wooden sliding door to the bedroom	_	_	_			
Front hood extension with plenty of storage space and two practical tensioning nets each on the right and left	•	•	•	•	•	•
Height-adjustable double bed	_	_	-	-		_
High-level single beds incl. comfortable access via steps	•		_		_	
Modern entrance shelf with practical storage compartments and tension straps	_					
Multifunctional storage space underneath the double bed incl. wardrobe, accessible from inside and outside, illuminated, bed frame adjustable	_	_	•	_	_	_
Overhead locker doors with soft-close function						
Overhead lockers in the rear area		•	_		_	
Seating area with mountable and extendible table and two integrated 3-point seatbelts  The practical tasking acts and on the quarker declaration the reached.						
Two practical tension nets under the overhead locker in the rear bed  Two practical tension nets under the overhead locker in the rear bed						
Wardrobe to the left and right of the queen-size bed						
Kitchen						
Fridge (137 l)						
Gourmet kitchen: two-ring hob, large drawers, cutlery tray, bin and generous worktop						
Kitchen backsplash with spice rule  MultiFlex rail system incl. hooks (further accessories via Dethleffs Original Accessories)						
Bathroom						
Equipped with cabinets, storage compartments, large mirrors, toothbrush mug and toilet paper holder						
Large bathroom with separate shower and toilet with locking door to the lounge	_	_	_	•	•	•
Swiveling bathroom wall for optimal use of space		-	-	-	_	_
Heating						
Digital control element for hot-air heating	•	•	•	•	•	•
Gas hot-air heating 6kW with hot-water boiler						
Heating in the seating unit for optimum heat distribution, built-in		•	•	•	•	•
Electrical installation						
Automatic switch-on/disconnect for starter battery, leisure battery and refrigerator	•	•	•	•	•	•
Awning light 12 V	•	•	•	•	•	•
Electric block with integrated overvoltage protection and separate ground fault circuit breaker					•	
Functional lighting (surface-mounted and recessed spotlights)	•			•	•	•
LED lighting throughout the vehicle					•	
Leisure battery AGM, 95 Ah	•	•	•	•	•	•
Number of sockets 1x 12V, 8x 230V, 4x USB						
On-board control panel	•	•	•	•	•	•
Spotlights in the roof lining above the habitation door	•	•	•	•	•	•
Water supply						
Fresh water tank in insulated and heated area	•		•	•	•	•
Submersible pump	•	•	•	•	•	•
Gas supply						
Storage space for 2 gas bottles with a filling weight of 11 kg each, with simplified access	•	•	•	•	•	•

O Optional equipment — Not possible lacktriangle Standard equipment lacktriangle Mandatory  $\Delta$  Not known at the time of publication

### PACKAGES TREND LOW PROFILE

Package	Package X (awning 3.5m) (13734)	Package X (awning 4.0m) (13734)	Package X (awning 4.5m) (13734)	0ne	One One	One	Package Two (awning 3.5m) (13733)	Two	Two
Integrated single-lens rear view camera	х	х	х	Х	х	х	х	Х	Х
Omnistor Cassette awning 3.5 m (manual)	Х			Х			х		
Omnistor cassette awning 4.0 m (manual)		х			х			Х	
Omnistor cassette awning 4.5 m (manual)			х			х			Х
Flat-screen TV bracket				Х	х	х	х	х	Х
Automatic HD satellite system 65 Twin				х	х	Х	х	х	Х
Flat screen 22" HD TV				х	х	Х			
Flat screen 32" HD TV							Х	Х	Х
Additional weight (kg)*	29.8	35	39	46.3	51.5	55.5	49.3	54.5	58.5

Package	Family Package T 6617 EB (14533)	Family Package T 6817, 7057 EB (14533)	Family Package T 6877 (14533)	Family Package T 7057 DBL (14533)	Family Package T 7057 EBL (14533)
Habitation door with window incl. blackout and central locking (incl. cab door)	Х	Х	Х	Х	Х
Cab blackout blinds	Х	Х	Х	Х	X
Light Moments: Indirect ambient lighting above the overhead lockers	Х	Х	Х	Х	х
Light Moments: Indirect wall surface ambient lighting	Х	Х	Х	Х	х
Light Moments: illuminated kitchen splashback	Х	Х	Х	Х	х
Light Moments: Clad seat chest side with indirect lighting	Х	Х	Х		
Cosy L-shaped seating group with free-standing, lowerable table base and 2 integrated 3-point belts	Х	Х	Х		
Option to convert single bed to double bed	Х	Х			Х
Light Moments: Indirect lighting in the bathroom with illuminated shower panel		Х	Х	Х	X
Light Moments: Entrance segment with indirect lighting		Х	Х	Х	Х
Additional weight (kg)*	26.1	26.7	19.2	9.7	17.2



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for

optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and explanations on the subject of weight can be found in the Legal information section.

Package	Winter Comfort Package ALDE T (13736)	Winter Comfort Package ALDE T (13736)	Winter Comfort Package ALDE T (13736)
Switch for water pump	Х	Х	Х
Insulated under-floor pipes	Х	Х	Х
Insulated waste water tank	Х	х	х
Waste water tank and pipes electrically heated	Х	х	Х
Hot-water carpet for the driver's cab	Х	х	х
Hot-water heating with boiler, automatic drain valve and shut-off valve for the sleeping area and digital control panel	Х	Х	
XPS insulation	Х		
XPS insulation		Х	
Hot-water heating with boiler, automatic drain valve and shut-off valve for the sleeping area and digital control panel			Х
XPS insulation			Х
Additional weight (kg)*	65.7	67.2	69.2

Package	Winter Comfort Package hot-air heating (13735)	Winter Comfort Package hot-air heating (13735)	Winter Comfort Package hot-air heating (13735)
Switch for water pump	Х	Х	Х
Insulated under-floor pipes	Х	Х	Х
Insulated waste water tank	Х	Х	Х
Waste water tank and pipes electrically heated	Х	х	х
Gas hot-air heating 6kW with 1.8kW electric heating element and hot-water boiler incl. digital control panel	Х	х	х
XPS insulation	Х		
XPS insulation		х	
XPS insulation			Х
Additional weight (kg)*	23.2	24.7	25.7

#### GT Design Package (14530)

 $\label{lem:continuous} \mbox{Double-glazed flush-fitting windows with blackout \& mosquito protection}$ 

Exterior design GT (rear light carrier with black diffuser, extended stickers, "red" skid plate)

Additional weight (kg)\*

2

#### Chassis Package (14476)

Automatic cab air conditioning, digital speedometer with 7" instrument cluster and wireless phone charger in the centre console

Electric parking brake

Full LED low beam

Additional weight (kg)\* -9.1



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for

optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and explanations on the subject of weight can be found in the Legal information section.

#### Assistance Package Fiat (14477)

Rain and light sensor with automatic dimming

Emergency Brake Assist with pedestrian detection

Lane Keep Assist

Traffic Sign Assist

Attention Assist

Intelligent speed assistant

Additional weight (kg)\*

0.5

#### Pre-wiring kit (11350)

Pre-wiring for solar

Pre-wiring for roof A/C

Pre-wiring for satellite system

Pre-wiring for first rear view camera

Pre-wiring for second rear view camera

Additional weight (kg)\*

7.6

△ Not known at the time of publication



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for

optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and explanations on the subject of weight can be found in the Legal information

Optional equipment*	Included in package	Additional weight (kg)*	Code	T 6617 EB	T 6817 EB	T 6877	T 7057 EB	T 7057 DBL	T 7057 EBL
Fiat chassis									
Fiat Ducato Light low platform (3,499 kg), MultiJet 140 (2.2 l / 103 kW / 140 hp), 8-speed torque converter automatic transmission	_	60	140A	0	0	0	0	0	0
Fiat Ducato Light low platform (3,499 kg), MultiJet 180 (2.2 l / 132 kW / 180 hp), 8-speed torque converter automatic transmission	_	60	180A	0	0	0	0	0	0
Fiat Ducato Maxi low platform (4,250 kg), MultiJet 180 (2.2 l / 132 kW / 180 hp), 8-speed torque converter automatic transmission	_	60	M180A	_	_	_	0	0	0
Weight upgrade									
Weight upgrade 3,650 kg	_	0	10769	0	0	0	0	0	0
Fiat chassis features									
Additional seat <sup>9)</sup>	_	14.5	435	_	_	0	0		_
Rear corner steadies (2 pieces)	_	6	390	0	0	0	0	0	0
Tow bar (check permissible gross towing weight for trailer operation)	_	62	273	0	_	_	_	_	_
Tow bar (check permissible gross towing weight for trailer operation)	_	65	273	_	0	0	_	_	_
Tow bar (check permissible gross towing weight for trailer operation)	_	66	273	_	=	_	0	0	0
Exterior features									
Bike rack for 3 bikes (lowerable)	_	20.7	7482	0	0	0	0	0	0
Bike rack for 3 bikes (rear)	_	10.5	938	0	0	0	0	0	0
Double floor in rear garage	_	10	1890	0	_	_	_	_	_
Double floor in rear garage	_	12	1890	_	0	_	0	0	0
Double floor in rear garage	_	13	1890	_	_	0	_	_	_
Double-glazed flush-fitting windows with blackout & mosquito protection	GT-P	1	415	0	0	0	0	0	0
Roof vent with fan	_	1.5	7507	0	0	0	0	0	0
Interior design									
Upholstery Heron (partial textile-leather)	_	0	13726	0	0	0	0	0	0
Upholstery Yoko	_	0	13725	0	0	0	0	0	0
Textile equipment									
Carpet, loose	_	5.4	851	0	_	_	_	_	_
Carpet, loose	_	5.9	851	_	0	_	_	_	_
Carpet, loose	_	5.3	851	_	_	0	_	_	_
Carpet, loose	_	6.8	851	_	_	_	0	_	_
Carpet, loose	_	8.3	851	_	_	_	_	0	_
Carpet, loose		7.3	851		_	_	_	_	0
Furniture layouts									
Bed convert for seating lounge transverse	_	5.5	1944	_	_	0	_	_	_
Bed convert for seating lounge transverse	_	7	1944	_	0	_	_	-	_
Bed convert for seating lounge transverse	_	8	1944	_	_	_	0	_	_
Bed convert for seating lounge transverse	_	5	1944	_	_	_	_	0	0
Electric pull-down bed across the seating unit 12)	_	65	13738	_	0	_	0	_	_
Electric pull-down bed across the seating unit 12)	_	68	13738	_	-	0	_	_	_
Electric pull-down bed across the seating unit <sup>12)</sup>	_	71	13738		_	_	_	0	0
Electric single pull-down bed above the seating area <sup>12)</sup>	_	45	13738	0	_	_	_	_	_
ISOFIX child seat bracket for third and fourth seat facing direction of travel	_	4	8125	0	0	0	0	_	_



INFO

The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and

explanations on the subject of weight can be found in the Legal information section. An increase of load capacity increases the manufacturer-specified mass for optional equipment. The increase results from the higher pay-mass due to the alternative chassis. The increased tare weight of the alternative chassis and, in particular, the weight for any mandatory heavier engine variants (e.g. 180 hp) must be deducted from this. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes.

Optional equipment*	Included in package	Additional weight (kg)*	Code	T 6617 EB	T 6817 EB	1 6877	T 7057 EB	T 7057 DBL	T 7057 EBL
Low single-beds for comfortable access and high headroom	_	-13	510	0	0	_	_	_	_
Low single-beds for comfortable access and high headroom	_	-10.5	510	_	_	_	0	_	0
Makeshift bed	_	7	339	0	_	_	_	_	_
Option to convert single bed to double bed	FA-P	7.5	1883	0	0	_	0	_	0
Kitchen									
Fridge (137 l) with integrated oven	_	12	290	_	_		0		
Fridge (137 I) with integrated oven	_	11	290	_	_	_	_	0	0
Bathroom			270						
		2	1/57	0	0	_	0	_	
Shower grate Window in bathroom	_	5	1657 372	0	0	0	0		0
		5	3/2		0	0	0	0	0
Multimedia									
Dethleffs Naviceiver incl. DAB+, truck navigation, wireless Apple CarPlay and Android Auto	_	3.65	9582	0	0	0	0	0	0
Second rear view camera in rear moulding	_	1	11541	0	0	0	0	0	0
	_		11541						
Heating		-	7.0			•	_	Ŷ	
Floor heating electric (partial) 14)	_	5	763	0	0	0	0	0	0
Gas hot-air heating 6kW with 1.8kW electric heating element and hot-water boiler incl. digital control panel	_	1	330	0	0	0	0	0	0
Hot-water carpet for the driver's cab <sup>13)</sup>	_	3.5	6709	0	0	0	0	0	0
Hot-water floor heating <sup>13)</sup>	-	11	1603	0	0	0	0	0	0
Hot-water heating with boiler, automatic drain valve and shut-off valve for the sleeping area and digital control panel	-	40	761	0	0	0	-	-	_
Hot-water heating with boiler, automatic drain valve and shut-off valve for the sleeping area and digital control panel	_	41	761	-	-	_	0	0	0
Electrical installation									
2nd Leisure battery Dual Battery System (Lithium), 140 Ah <sup>7)</sup>	_	19	13968	0	0	0	0	0	0
Second leisure battery AGM, 95 Ah 7)	_	27	830	0	0	0	0	0	0
Solar power system 100 watt	_	12.6	922	0	0	0	0	0	0
Water supply									
Insulated waste water tank	_	11	13742	0	0	0	0	0	0
Outdoor shower (cold water)	_	0.5	793	0	0		0		0
Switch for water pump	-	0.2	397	0	0	0	0	0	0
Gas supply									
Automatic gas cylinder switchover incl. crash sensor, EisEx and gas filter	_	2.5	1577	0	0	0	0	0	0
Outdoor gas socket gas pressure 30 mbar	_	1.3	878	0				0	
Safety									
2 kg fire extinguisher	_	4	1878	0	0	0	0	0	0
Safe	_	4.7	13739	0	0	0	0	0	0
Smoke detector	_	0.2	1891	0	0	0	0	0	0
Packages									
Assistance Package Fiat	_	0.5	14477	0	0	0	0	0	0
Chassis Package	_	-9.1	14476	0	0	0	0	0	0
Family Package T 6617 EB	_	26.1	14533	0	-	_	_	_	_



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for actional equipment change in the model programs. This is a calculated to the control of the selected optional equipment change in the model programs. This is a calculated to the control of the selected optional equipment in the model programs. optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and

explanations on the subject of weight can be found in the Legal information section. An increase of load capacity increases the manufacturer-specified mass for optional equipment. The increase results from the higher pay-mass due to the alternative chassis. The increased tare weight of the alternative chassis and, in particular, the weight for any mandatory heavier engine variants (e.g. 180 hp) must be deducted from this. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes. footnotes.

Optional equipment*	Included in package	Additional weight (kg)*	Code	T 6617 EB	T 6817 EB	T 6877	T 7057 EB	T 7057 DBL	T 7057 EBL
Family Package T 6817, 7057 EB	_	26.7	14533	_	0	_	0	_	_
Family Package T 6877	_	19.2	14533	_	_	0	_	_	_
Family Package T 7057 DBL	_	9.7	14533	_	_	_	_	0	_
Family Package T 7057 EBL	_	17.2	14533	_	_	_	_	_	0
GT Design Package	_	2	14530	0	0	0	0	0	0
Package One (awning 3.5m)	_	46.3	13732	0	_	_	_	_	_
Package One (awning 4.0m)	_	51.5	13732	_	0	0	_	_	_
Package One (awning 4.5m)	_	55.5	13732	_	_	_	0	0	0
Package Two (awning 3.5m)	_	49.3	13733	0	_	_	_	_	_
Package Two (awning 4.0m)	_	54.5	13733	_	0	0	_	_	_
Package Two (awning 4.5m)	_	58.5	13733	_	_	_	0	0	0
Package X (awning 3.5m)	_	29.8	13734	0	_	_	_	_	_
Package X (awning 4.0m)	_	35	13734	_	0	0	_	_	_
Package X (awning 4.5m)	_	39	13734	_	_	_	0	0	0
Pre-wiring kit	_	7.6	11350	0	0	0	0	0	0
Winter Comfort Package ALDE T	_	65.7	13736	0	_	_	_	_	_
Winter Comfort Package ALDE T	_	67.2	13736	_	0	0	_	_	_
Winter Comfort Package ALDE T	_	69.2	13736	_	_	_	0	0	0
Winter Comfort Package hot-air heating	_	23.2	13735	0	_	_	_	_	_
Winter Comfort Package hot-air heating	_	24.7	13735	_	0	0	_	_	_
Winter Comfort Package hot-air heating	_	25.7	13735	_	_	_	0	0	0
Miscellaneous									
Registration documents (CoC papers)	_	0	15152	•	•	•	•	•	<b>*</b>

O Optional equipment — Not possible Standard equipment lack Mandatory  $\Delta$  Not known at the time of publication

GT-P GT Package FA-P Family Package



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and

explanations on the subject of weight can be found in the Legal information section. An increase of load capacity increases the manufacturer-specified mass for optional equipment. The increase results from the higher pay-mass due to the alternative chassis. The increased tare weight of the alternative chassis and, in particular, the weight for any mandatory heavier engine variants (e.g. 180 hp) must be deducted from this. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes. footnotes.

#### **LEGAL NOTES ON WEIGHT-RELATED INFORMATION**

The weight specifications and tests for **motorhomes** are uniformly regulated throughout the EU in EU Implementing Regulation No. 2021/535 (until June 2022: EU Implementing Regulation No. 1230/2012). We have summarised and explained the key terms and legal requirements from this **regulation** for you below. Our **dealers** and the Dethleffs configurator on our website offer you additional assistance in configuring your vehicle.

#### 1. Technically permissible maximum laden mass

The technically permissible maximum laden mass of the vehicle (e.g. 3,500 kg) is a mass specification set by the manufacturer which the vehicle must not exceed. Information on the technically permissible maximum laden mass of the model you have chosen can be found in the technical data. If the vehicle exceeds the technically permissible maximum laden mass in everyday driving, this constitutes an administrative offence which may result in a fine.

#### 2. Mass in running order

In simple terms, the mass in running order is the basic vehicle with standard equipment plus a legally fixed standard weight of 75 kg for the driver. This essentially includes the following items:

- the unladen weight of the vehicle together with the bodywork, including operating fluids such as greases, oils and coolants;
- the **standard equipment**, i.e. all equipment items that are included as standard in the factory-fitted scope of delivery;
- the fresh water tank filled to 100 % in driving mode (driving fill according to manufacturer's specifications;) and an aluminium gas cylinder filled to
- the fuel tank, which is 90 % full, including fuel;
- the driver, whose weight regardless of the actual weight is generally specified as 75 kg in accordance with EU law.

Information on the **mass in running order** can be found for each model in our sales documents. It is important to note that the value for **mass in running order** given in the sales documents is a default value determined in the **type-approval procedure** and verified by the authorities. It is legally permissible and possible for the **mass in running order** of the vehicle delivered to you to deviate from the nominal value stated in the sales documents. The legally permissible **tolerance** is  $\pm$  5 %. In this way, the EU legislator accounts for the fact that certain fluctuations in the **mass in running order** occur due to variations in the weight of supplied parts as well as due to processes and weather conditions.

These weight deviations can be illustrated by means of an example calculation:

- Mass in running order acc. to sales documents: 2,850 kg
- Legally permissible tolerance of ± 5 %: 142.50 kg
- Legally permissible range of **mass in running order**: 2,707.50 kg to 2,992.50 kg

The specific range of permissible weight deviations can be found for each model in the technical data. Dethleffs makes great efforts to reduce weight variations to the minimum that is unavoidable for production reasons. **Deviations** at the upper and lower end of the range are therefore very rare; however, they cannot be completely ruled out technically, even

with all optimisations. The real weight of the vehicle and compliance with the permissible **tolerance** is therefore checked by Dethleffs by weighing each vehicle at the **end of the line**.

#### 3. Mass of the passengers

The **mass of the passengers** is set a standard value of 75 kg for each seat provided by the manufacturer, regardless of the actual weight of the passengers. The **mass of the driver** is already included in the **mass in running order** (see no. 2 above) and is therefore not included again. In the case of a **motorhome** with four **permitted seats**, the **mass of the passengers** is therefore 3 \* 75 kg = 225 kg.

#### 4. Optional equipment and actual mass of the vehicle

**Optional equipment** (also: additional equipment) includes, according to the legal definition, all optional equipment parts not included in the **standard equipment** which are fitted to the vehicle under the responsibility of the manufacturer – i.e. ex works – and can be ordered by the customer (e.g. awning, bicycle or motorbike carrier, satellite system, solar system, oven, etc.). Information on the individual or package weights of the **optional equipment** that can be ordered can be found in our sales documents. **Optional equipment** in this sense does not include other **accessories** that are retrofitted by the **dealer** or you personally after the vehicle has been delivered ex works.

The mass of the vehicle in running order (see no. 2 above) and the mass of the optional equipment fitted to a specific vehicle at the factory are together referred to as the actual mass. You will find the corresponding information for your vehicle after handover under item 13.2 of the Certificate of Conformity (CoC). Please note that this specification also represents a standardised value. Since the mass in running order – as an element of the actual mass – is subject to a legally permissible tolerance of  $\pm~5~\%$  (see no. 2), the actual mass may also deviate accordingly from the stated nominal value.

#### 5. Pay-mass and minimum pay-mass

The installation of optional equipment is also subject to technical and legal limits: Only so much optional equipment can be ordered and fitted at the factory that sufficient free weight remains for baggage and other accessories ("pay-mass") without exceeding the technically permissible maximum laden mass. The pay-mass is calculated by subtracting the mass in running order (nominal value according to sales documents, see no. 2 above), mass of the optional equipment and the mass of the passengers (see no. 3 above) from the technically permissible maximum laden mass (see no. 1 above). The EU regulations stipulate a fixed minimum pay-mass for motorhomes, which must remain as a minimum for baggage or other non-factory-fitted accessories. This minimum pay-mass is calculated as follows:

Minimum pay-mass in kg ≥ 10 \* (n + L)

Where: "n" is the maximum number of passengers plus the driver and "L" is the overall length of the vehicle in metres.

For a motorhome with a length of 6 m and 4 approved seats, the minimum pay-mass is therefore e.g. 10 kg  $^*$  (4 + 6) = 100 kg.

To ensure that the minimum pay-mass is maintained, there is a maximum combination of optional equipment that can be ordered for each vehicle model. In the above example with a minimum pay-mass of 100 kg, the total mass of optional equipment for a vehicle with four permitted seats and a mass in running order of 2,850 kg should not exceed 325 kg:

3,500 kg technically permissible maximum laden mass

- 2,850 kg mass in running order
 - 3\*75 kg mass of the passengers
 - 100 kg minimum pay-mass

= 325 kg maximum permissible mass of **optional equipment** 

It is important to note that this calculation is based on the default value for mass in running order as defined in the type-approval procedure, without taking into account the permissible weight deviations for mass in running order (see no. 2 above). If the maximum permissible value for the optional equipment of (in the example) 325 kg is almost or completely exhausted, an upward weight deviation can therefore result in the minimum pay-mass of 100 kg being met mathematically using the default value for the mass in running order, although in fact there is no corresponding load capacity. Here, too, an example calculation for a vehicle with four seats, whose real weighed mass in running order is 2 % above the nominal value:

3.500 kg technically permissible maximum laden mass
- 2.907 kg real weighed mass in running order (+ 2 % compared to the stated value of 2,850 kg)
- 3\*75 kg mass of the passengers

- 325 kg optional equipment (maximum permissible value)
 = 43 kg actual load capacity (< minimum pay-mass of 100 kg)</li>

In order to avoid such a situation, Dethleffs further reduces the maximum permissible weight of the total **optional equipment** that can be ordered on a model-specific basis. The limitation of **optional equipment** is intended to ensure that the **minimum pay-mass**, i.e. the legally prescribed free mass for **baggage** and retrofitted **accessories**, is actually available for the **vehicle load capacity** of the vehicles delivered by Dethleffs. Since the weight of a specific vehicle can only be determined when it is weighed at the **end of the line**, in very rare cases a situation may arise in which the **minimum pay-mass** at the **end of the line** is not guaranteed, despite this limitation of **optional equipment**. In order to guarantee the **minimum pay-mass** even in these cases, Dethleffs will check together with your **trade partner** and you before delivery of the vehicle whether, for example, the vehicle is loaded up, seats are reduced or **optional equipment** is removed.

## 6. Effects of tolerances of the mass in running order on the pay-mass

Regardless of the minimum pay-mass, you should note that unavoidable production-related fluctuations in the mass in running order – both upwards and downwards – have a mirror-image effect on the remaining load capacity: If you order our example vehicle (see no. 3. above), for example, with optional equipment with a total weight of 150 kg, the calculated pay-mass based on the default value for the mass in running order is 275 kg. The load capacity actually available may deviate from this value due to tolerances and may be higher or lower. If the mass in running or-

**der** of your vehicle is, for example, permissibly 2 % higher than stated in the sales documents, the **load capacity** is reduced from 275 kg to 218 kg:

3.500 kg technically permissible maximum laden mass

2.907 kg  $\,$  real weighed mass in running order (+ 2 % compared to the

stated value of 2,850 kg) 3\*75 kg mass of the passengers

150 kg **optional equipment** ordered for the specific vehicle

= 218 kg sactual load capacity

As a precaution to ensure that the calculated pay-mass is actually given, you should therefore take the possible and permissible tolerances for the mass in running order into account when configuring your vehicle. We also recommend that you weigh the laden motorhome on a non-automatic scale before each journey and, taking the individual weight of the passengers into account, determine whether the technically permissible maximum laden mass and the technically permissible maximum mass on the axle are observed.